

# Welcome

## An introduction from our President

| Industry-leading 2D X-ray units                     |    |
|---|----|
| Planmeca ProMax® 2D                                 | 6  |
| The benchmark for extraoral imaging                 | 6  |
| Effortless and comfortable                          | 8  |
| Robotic arm technology                              | 10 |
| All the imaging programs you need                   | 12 |
| Quality cephalometry for orthodontics               | 14 |
| Easy upgrade from 2D to 3D                          | 16 |
| Planmeca ProOne®                                    | 18 |
| Simplicity at its finest                            | 18 |
| Optimal imaging programs                            | 20 |
| Planmeca ProX™                                      | 22 |
| Flexible intraoral X-ray unit                       | 22 |
| Planmeca ProSensor® HD                              | 24 |
| Innovative intraoral sensor                         | 24 |
| Planmeca ProScanner® 2.0                            | 26 |
| User-friendly and reliable imaging plate scanner    | 26 |
| Planmeca Romexis® – one software for all your needs | 28 |
| High-performance 2D imaging                         | 30 |
| Share images and expertise online                   | 32 |
| Technical specifications                            | 3/ |

"It's my great pleasure to introduce you to our pioneering 2D X-ray units. Our comprehensive range of digital units meets all your daily imaging needs – working perfectly with our highly advanced **Planmeca Romexis®** software for the most detailed extraoral and intraoral examinations possible.

I'm extremely proud of our product innovations, and for over 45 years we've worked closely with dental professionals to set new standards in our field. What makes us a bit different is that all core product development and manufacturing takes place at our headquarters in Helsinki, Finland – ensuring exceptional quality and unmatched attention to detail at every stage of the process.

We also have a dedicated team of R&D professionals behind the scenes, developing breakthrough innovations that make a real difference. Our robotic SCARA technology, for example, offers flexible, precise and complex movements needed for extraoral maxillofacial imaging. Our Planmeca ProMax® 2D X-ray units are all 3D-ready, which means you can easily upgrade at a later point.

I am thrilled to invite you to discover our world of 2D imaging!"

**Heikki Kyöstilä** President and founder Planmeca Group



# Industry-leading 2D X-ray units

Explore our world-class range of 2D imaging equipment – offering the most advanced and versatile features and software to meet all your 2D extraoral and intraoral imaging needs.





Planmeca ProScanner® 2.0

# Planmeca ProMax® 2D

# The benchmark for extraoral imaging

*Planmeca ProMax*® is a complete maxillofacial imaging system. The design and operation principles are based on the latest scientific research, technological innovations and the most demanding needs of modern-day radiology.

## Different models for different needs

#### Planmeca ProMax® 2D S3

The three-joint model (SCARA3) Planmeca ProMax® 2D S3 has been designed for all imaging needs: panoramic, true extraoral bitewing, TMJ, sinus and 2D tomography.

#### Planmeca ProMax® 2D S2

The two-joint model (SCARA2) Planmeca ProMax® 2D S2 includes basic programs for panoramic, extraoral bitewing, TMJ and sinus imaging.

## **Key features**

#### Advanced technology

- Autofocus positions the focal layer automatically for perfect panoramic images
- Dynamic Exposure Control (DEC) measures the patient's radiation transparency and automatically adjusts exposure values
- Patented SCARA (Selectively Compliant Articulated Robot Arm) technology guarantees an anatomically accurate imaging geometry for clear, error-free images
- Easy upgrades add cephalostat or 3D imaging capability at any time


- · Full-view patient positioning with triple-laser patient positioning lights
- Easy-to-use graphical interface
- on the imaging workstation
- · TWAIN support and full DICOM compliance













# Effortless and comfortable

Our industry-leading **Planmeca ProMax**® unit is known across the world for incredible ease of use and exceptional patient comfort. A relaxed patient means a smooth imaging workflow and the best possible image quality.



#### Open patient positioning

- Position patients effortlessly thanks to open-face architecture
- · Correct patient positioning either with Autofocus or manually
- Make fine adjustments using positioning lasers and joystick
- · Work with an unrestricted view of your patient
- · Avoid claustrophobic feelings in patients
- Accommodate wheelchairs easily with side-entry access

#### Laser-assisted patient alignment

- A triple laser beam system accurately indicates the correct anatomical alignment points for patient positioning
- · The midsagittal plane positioning beam indicates the correct sideways alignment
- The Frankfort horizontal plane positioning beam shows the correct forward tilt of your patient's head
- · The focal layer positioning beam indicates the focal layer position and ensures images are sharp and clear
- Fine adjustments can be made using the joystick

#### **User-friendly control panel**


- Clear and straightforward graphical user interface guides you smoothly through your work
- Pre-programmed sites and exposure values for different image types and targets save you time and allow you to focus on your
- The control panel can also be operated remotely from the imaging workstation


#### Improved image quality with **Dynamic Exposure Control (DEC)**


The unique digital Dynamic Exposure Control (DEC) automatically adjusts the exposure values for each individual patient based on their anatomic structure and bone density. DEC improves the quality of both panoramic and cephalometric imaging with more consistent brightness and contrast.

#### Adjustable focal layer

Developed based on scientific research, the imaging geometry matches the shape of the focal layer with the patient's anatomy, resulting in clear panoramic radiographs. Simply select the shape of the focal layer on the graphical user interface, according to the size and shape of the patient's jaw.









# Robotic arm technology

Planmeca ProMax® features highly advanced and exclusive robotic SCARA (Selectively Compliant Articulated Robot Arm) technology – providing flexible, precise and complex movements required for rotational maxillofacial imaging.



#### Unlimited movement range

Our revolutionary SCARA technology combines an electro-mechanical construction with real-time computation of dynamic rotation patterns. This enables optimised radiography for each individual patient, meeting virtually any diagnostic requirement for maxillofacial dentistry.

#### **User benefits for SCARA**

The precise free-flowing arm movements allow for a wider variety of imaging programs not possible with other X-ray units with fixed rotations. SCARA offers superior imaging capabilities for both existing and future technologies.

#### Perfect panoramic images – every time

Positioning errors are now a thing of the past – with SCARA technology you can take an ultra-low-dose scout image of your patient's central incisors for a fast diagnostic panoramic image every time.

#### **Two options**

- The three-joint model (SCARA3) Planmeca ProMax® 2D S3 for all imaging needs.
- The two-joint model (SCARA2) Planmeca ProMax® 2D S2 for basic imaging needs.


## Special features only possible with our SCARA3 technology

#### X-ray unit recognises your patient's anatomy

The unique Autofocus feature automatically positions the focal layer using a low-dose scout image of the patient's central incisors. It uses landmarks in the patient's anatomy to calculate placement, enabling practically error-free patient positioning and dramatically reducing the need for retakes. The result is a perfect panoramic image.

#### Better diagnostic value with extraoral bitewings

- · Ideal for all patients no sensor positioning required
- · Consistently opens interproximal contacts, giving better diagnostic value
- · Larger diagnostic area than in intraoral modalities
- · More clinical data: canine to third molar
- Enhanced clinical efficiency takes less time and effort than conventional intraoral bitewings







# All the imaging programs you need




Standard panoramic




PA TMJ (closed & open)




Lateral TMJ (closed & open)



Longitudinal tomography




True bitewing




Horizontal and vertical segmenting



Lateral sinus and PA linear sinus







Combined tomograph

Our **Planmeca ProMax**® X-ray unit offers the widest variety of imaging programs available – easily meeting all your clinical needs.

#### **Panoramic imaging**

In addition to the Standard panoramic program, the following programs are offered:

- Interproximal panoramic program: generates an image, where interproximal teeth contacts are open. Primarily used for caries detection.
- Orthogonal panoramic program: produces an image with clearly visible alveolar crest for improved diagnostics. Ideal for periodontal imaging and implant planning.

#### **Extraoral bitewings**

The Bitewing program uses improved interproximal angulation geometry. The result is a bitewing image pair with low patient dose and excellent diagnostic quality.

# Horizontal and vertical segmenting for panoramic program

With the Horizontal and vertical segmenting program, exposure can be strictly limited to the diagnostic region of interest. Patient dosage is reduced by up to 90% compared to full panoramic exposure.

#### TMJ imaging

The TMJ imaging programs produce lateral or posteroanterior views of open or closed temporomandibular joints. The imaging angle and position can be adjusted to correspond to the anatomy of each individual patient.


The Lateral-PA TMJ program captures lateral and PA views on the same radiograph. The multi-angle TMJ programs produce radiographs with images from three different angles, from either the lateral or PA view.

#### Sinus imaging

The Sinus programs provide a clear view of the maxillary sinuses.

#### **Tomographic imaging**

Planmeca ProMax® 2D tomography programs provide accurate tomographic information for the analysis, planning and follow-up of implant and surgical procedures.



#### Child mode for reduced dose

Child mode reduces the patient dose remarkably for all programs by reducing the imaging area and exposure values. In the panoramic program the focal layer can also be narrowed.

Quality cephalometry for orthodontics

Our exceptional equipment and advanced software have been designed to meet all your orthodontic needs.

# Cephalometric imaging with Planmeca X-ray units

- The functional and easy-to-use head positioner ensures accurate positioning for all cephalometric projections
- The carbon fibre ear posts and nasal positioner are extremely stable, hygienic, and transparent to radiation
- The unit automatically aligns itself to take cephalometric exposures and then selects a corresponding collimator
- Dedicated collimation options for paediatric imaging



## Two equipment options:


#### One-shot Planmeca ProCeph™ cephalostat

- Effective one-shot cephalostat
- Short exposure time no motion artefacts, low patient dose
- Image sizes from 18 x 20 cm to 30 x 25 cm
- Available for all Planmeca 3D X-ray units

#### Scanning Planmeca ProMax® cephalostat

- Digital cephalostat that scans your patient's head horizontally using a narrow X-ray beam with an extremely low effective dose of radiation
- Exceptional flexibility in image formats, with field sizes of up to 30 x 27 cm





## Two options for cephalometric analyses:

#### Planmeca Romexis® Cephalometric Analysis module

Take advantage of the **Planmeca Romexis® Cephalometric Analysis** module's wide range orthodontic and orthognathic tools.

- · Automatic landmark identification
- Tools for creating cephalometric analyses, superimpositions, and surgical treatment plans (VTO) in minutes
- Fully customisable analyses, norms, and reports
- Microsoft Excel export and import function
- Compatible with the Windows operating system

#### Online automatic analysis service

Acquire cephalometric analyses regardless of time and place with the **Planmeca Romexis®** automatic cephalometric analysis service.

- Online automatic cephalometric tracing in a few seconds
- Over 50 analyses available for download immediately after tracing
- Direct link from the Planmeca Romexis 2D module for ordering analyses

# Easy upgrade from 2D to 3D



## Planmeca ProMax® – future proof and a great investment

Planmeca ProMax® 2D is designed with upgradeability in mind. The unit's modular structure allows easy conversion to different imaging modalities, while the software-driven SCARA is extremely flexible, allowing you to benefit from new imaging projections.

Whether you're upgrading your 2D unit to 3D, or adding a cephalometric arm, Planmeca has the right solution for you.

Individual options can be installed before delivery or added later, making Planmeca ProMax the most versatile all-in-one X-ray unit available.









#### **Update options**

Planmeca ProMax 2D S3 Planmeca ProMax 2D S2

PLANMECA | 17

# Planmeca ProOne®

Simplicity at its finest



**Planmeca ProOne**® is our full-featured panoramic X-ray unit. It has been designed with simplicity in mind and features several cutting-edge innovations – combining extensive diagnostic capabilities and superior image quality into a compact, easy-to-use package.

#### **Easy patient positioning**

To minimise imaging errors caused by incorrect patient positioning, Planmeca ProOne and all our other X-ray units support open positioning and convenient side entry for patients - both standing and seated. You can monitor your patient from the front and the side, with positioning further assisted by our triple laser beam system that indicates the correct anatomical positioning points.

#### User interface provides guidance

Planmeca ProOne is equipped with a full-colour graphical user interface to help guide you through procedures with clear texts and symbols. All settings are logically organised and easy to understand, which speeds up the imaging process and lets you focus on communicating with your patient and positioning them correctly.

#### Autofocus – for perfect panoramics every time

Our unique **Autofocus** feature automatically positions the focal layer using a low-dose scout image of your patient's central incisors. Landmarks in the patient's anatomy are used to calculate placement, enabling practically error-free patient positioning and dramatically reducing the need for retakes. The result is a perfect panoramic image, every time.


| Panoramic imaging  | ·        |
|--------------------|----------|
| Extraoral bitewing | <b>v</b> |
| TMJ imaging        | <b>v</b> |
| Sinus imaging      | <b>v</b> |
| Child mode         | <b>v</b> |
| Autofocus          | <b>/</b> |

# Optimal imaging programs











PA Sinus and Lateral non rotational sinus



Horizontal and vertical segmenting for panoramic program







*Planmeca ProOne*® offers you a wide variety of imaging programs for different radiographic needs. You can also select the correct exposure formats to minimise the radiation dose for all types of patients and diagnostic purposes.

#### **Imaging programs**

| Standard: Basic panoramic programs    | Standard panoramic  |
|---------------------------------------|---|
|                                       | Lateral TMJ   |
|                                       | PA TMJ  |
|                                       | PA Sinus  |
| Standard                              | Child (Paediatric) mode for each program to reduce the dose |
| Optional                              | Horizontal and vertical segmenting for panoramic program    |
| Optional                              | Bitewing  |
| Optional: Advanced panoramic programs | Interproximal panoramic                                     |
|                                       | Orthogonal (perio) panoramic                                |
|                                       | Lateral-PA TMJ  |
|                                       | Lateral multiangle TMJ                                      |
|                                       | Lateral non rotational sinus                                |
|                                       | Cross-sections  |
|                                       | Bitewing  |

#### Child mode for optimal paediatric imaging

In child mode, the imaging area and exposure values are reduced in all programs and also the focal layer can be narrowed in the panoramic program. The patient dose is reduced remarkably.





20 PLANMECA PLANMECA 21

# Planmeca ProX<sup>™</sup>

## Flexible intraoral X-ray unit

Our advanced **Planmeca ProX™** unit provides easy and precise positioning, a straightforward imaging process and top-quality images in high resolution. It is a highly beneficial and effective 2D imaging option for all dental clinics, making intraoral imaging easier and more reliable than ever.

#### The premium intraoral X-ray unit

- Optimal images for all diagnostic needs: variable kV and mA
- Quick and easy to use: pre-programmed quick settings, practical design
- · Digital-ready
- · Integration with the Planmeca ProSensor® HD intraoral sensor
- Smooth workflow with the Planmeca Romexis® software
- Versatile installation options

#### Highly adaptable imaging

Planmeca ProX™ adapts to both short-cone and long-cone imaging. For maximum radiation hygiene, an additional rectangular collimator can be adapted to the long cone. The steady X-ray unit arm provides accurate and drift-free positioning of the lightweight tube head.

#### **Quick imaging parameter settings**

Planmeca ProX comes pre-programmed with quick settings for different exposure value combinations. Imaging parameters are automatically retrieved according to the selected exposure region and diagnostic need. Values can also be manually adjusted if necessary. Simply select the image receptor to automatically adapt the pre-programmed settings for film, imaging plate or digital sensors – allowing rapid transition to new imaging technologies without reprogramming.

#### Faster X-ray examinations with digital sensor

Benefit from the the most user-friendly intraoral imaging by combining Planmeca ProX with the Planmeca ProSensor HD intraoral sensor. The captured image is displayed on the screen just seconds after exposure, significantly reducing the time needed for an intraoral X-ray examination compared to conventional film.

#### **Numerous installation options**

As every dental clinic is different, it is important to offer various ways to integrate equipment. Planmeca ProX can be installed to match the individual layout and workflow of any type of clinic.





# Planmeca ProSensor® HD

#### Innovative intraoral sensor

Our innovative Planmeca ProSensor® HD intraoral sensor offers a unique combination of unparalleled image quality, patient-centred design, and usability. The sensor has been designed to last and provides durability that can be counted on.

#### **Cutting-edge image quality**

With a true resolution of over 20 lp/mm, Planmeca ProSensor® HD offers real HD image quality. Supporting detailed diagnosis, the advanced imaging sensor with a fibre-optic layer captures sharp, low-noise and high contrast images. The wide dynamic range of the sensor ensures successful results each and every time.

#### Patient-centred design

To fulfill all intraoral imaging needs, Planmeca ProSensor HD is available in three different sizes. The rounded sensor edges make procedures comfortable for patients, with outstanding images ready in a matter of seconds.

#### **Intraoral X-ray unit integration**

The seamless integration of Planmeca ProSensor HD with the Planmeca ProX<sup>™</sup> intraoral X-ray unit ensures convenience and efficiency at every step. The sensor is easy to connect using just one hand.


#### **High-end usability**

The intraoral sensor's magnetic connector makes it easy to attach, with its white colour enhancing visibility to further ease positioning. The sensor's elegant control box is equipped with a colour-coded LED light that provides instant visual feedback of the imaging procedure, while its hermetically sealed housing ensures effective infection control.

#### Carefree choice

Intraoral sensors are naturally subject to wear and tear in daily use, but Planmeca ProSensor HD has been built to last. The sensor's carbon fibre plate prevents bite marks, its shock protection layer guards against minor damage, and its strengthened cable further improves durability.


#### Each layer carefully designed – for perfect results



#### Planmeca ProSensor® HD in a nutshell

- True resolution of over 20 lp/mm
- · Sharp and low-noise images with high contrast
- · Wide dynamic range
- Three sensor sizes with rounded edges
- · Magnetic connector for ease of use
- · Colour-coded LED light on control box for instant visual feedback
- · Integration with the Planmeca ProX intraoral X-ray unit
- Fully compatible with Windows and Mac
- · Plug and play USB version
- Five-year warranty program two years upon registering the product with the opportunity to purchase three additional years





# Planmeca ProScanner® 2.0

## User-friendly and reliable imaging plate scanner

Our new **Planmeca ProScanner® 2.0** imaging plate scanner is a high-quality option for fast and dependable intraoral imaging. With intelligent design details and outstanding durability, the scanner supports everyday tasks at a dental clinic – providing reliability that is hard to match.

#### Reliable and dependable

Planmeca ProScanner® 2.0 has been designed to be a seamless part of your clinic's workflow. It is a true workhorse imaging plate scanner that is maintenance-free and extremely durable. The compact scanner fits into any room, helping all clinics prevent downtime and ensure maximum efficiency.

#### **Smart imaging plates**

Planmeca ProScanner 2.0 utilises RFID technology for fast scanning and identification. The scanner's high-quality plates can be used numerous times and the integrated eraser instantly prepares them for further imaging. The flexible and bendy imaging plates are very comfortable for patients and available in the most common sizes – 0, 1, and 2.

#### Easy to use

Planmeca ProScanner 2.0 significantly speeds up your intraoral imaging workflow with its fast scanning process. Just insert the imaging plate, scan it and diagnose the captured image. If the wrong side of the plate is accidentally exposed, it is easy to notice immediately from the captured image.

#### Planmeca Romexis® software integration

Each imaging plate is equipped with a digital serial number so you can sort, view, and compare images for quality control, as well as count exposures by using the serial number of each plate in the Planmeca Romexis® software.





# Planmeca Romexis® – one software for all your needs

We offer a revolutionary all-in-one software solution for clinics of all sizes. Our world-leading **Planmeca Romexis**® software is the brains behind all of our products, bringing together all the devices at your dental clinic from CAD/CAM to imaging devices and dental units. The easy-to-use Romexis supports the most versatile range of 2D and 3D imaging modalities.

Mac and Windows compatible



# High-performance 2D imaging

Our advanced **Planmeca Romexis®** software platform offers the most versatile tools for 2D imaging. Diagnose images using our full range of enhancement tools – or view them wherever you are with our mobile apps. This flexible dental imaging software adapts to your needs and will grow into the third dimension together with your practice.



#### Easy and powerful

**Planmeca Romexis®** is the software of choice for viewing and processing 2D images from Planmeca X-ray units. Powerful enhancement and analysis tools help users in all specialties reach accurate diagnoses, while the intuitive interface guarantees confident and comfortable usability from day one.


#### Open and compatible

Planmeca Romexis stores all patient 2D images in one centralised database – from X-ray images to photos and even videos. All images are available in the network immediately and can always be exported in standard formats. Our integration with other systems allows you to freely utilise third-party product at your clinic. TWAIN support and DICOM standard compliance ensure that software can be used with most systems.



#### Integrated document management

With Romexis, it is easy to create professional, high-quality printouts and radiology reports to be sent to referring dentists – with multi-page support included. Documents of any type can be attached to patient files, ensuring convenient storage for cephalometric tracing reports, referral letters, and other relevant information.



#### Advanced implant planning

Planmeca Romexis provides powerful tools for implant planning, including realistic implant models from over 80 manufacturers. You can find the constantly growing list of all the implants included in the implant library at planmeca.com/Romexisimplantlibrary.





# Share images and expertise online

**Planmeca Romexis® Cloud** is a secure image transfer service for **Planmeca Romexis®** users and their partners for sharing image and patient data with any specialist or patient. You can share images and expertise securely with all partners who use Planmeca Romexis, the free Planmeca Romexis® Viewer, or the **Planmeca mRomexis**<sup>™</sup> mobile tablet application.

#### Versatile possibilites for communication

- External applications, CDs and DVDs are history images can now be sent directly from Planmeca Romexis®
- The Romexis software and a Planmeca Romexis® Cloud subscribtion are required to send new cases – recipients only need an email account
- Dental labs can receive CAD/CAM cases without additional
- Cases can also be viewed with the Planmeca Romexis® Viewer or **Planmeca mRomexis**<sup>™</sup> applications

Visit online.planmeca.com


to subscribe and start sending images now.

#### Recieve cases with free Planmeca Romexis® Viewer application

Planmeca Romexis Viewer is a free application that can be exported and sent together with images from Planmeca Romexis.

- Full-featured viewer application
- · No installation required
- · Mac and Windows support
- Distribute to specialists or patients

Visit planmeca.com/Viewer for downloading Planmeca Romexis Viewer software.



Cephalometric

Interpretations

· Treatment plans

Intraoral

Photo

· Referrals

- · Radiology center
- · General practice

- General practitioner
- Colleague
- Radiologist
- Specialist
- Dental lab
  - Patient



#### Increased flexibility with Planmeca mRomexis<sup>™</sup> tablet application

Use our fast, easy, and light Planmeca mRomexis mobile imaging application to view all your images in the Planmeca Romexis database on a local network, or to carry images with you on your tablet device. You can also use the application to capture 2D X-ray images with Planmeca equipment, or to take photos with the

Download the Planmeca mRomexis application for iOS and Android from the App Store or Google Play.








# Access to unique X-ray device data

Take the efficiency of your clinic to the next level with real-time information on networked equipment usage and events. Our Romexis® **Clinic Management** software offers several quality assurance and service benefits for local users, whereas **Romexis**® **Insights** allows you to remotely monitor your clinic from anywhere.

Planmeca equipment can be networked to gather valuable data on their use.

- Detailed X-ray log book with dosage and sensor information
- · Meet regulatory requirements with automatic recording of image exposure values: kV and mAs
- Enhanced operational planning exposure counts and modality distribution
- Enhance operational planning usage hours
- Use detailed event logs to improve quality assurance including radiation hygiene
- Maximise equipment uptime with fast and accurate trouble-shooting



## Planmeca ProMax® 2D

# Technical specifications


#### **Technical data**


| Generator                         | Constant potential, resonance mode high frequency 80–150 kHz |   |
|-----------------------------------|--|---|
| X-ray tube                        | D-054SB-P  |   |
| Focal spot size                   | 0.5 x 0.5 mm (IEC 336)                                       |   |
| Total filtration                  | min. 2.5 mm Al eq  | uivalent                                  |
| Anode voltage                     | 50-84 kV   |   |
| Anode current                     | 0.5–16 mA DC   |   |
| Exposure time                     | Pan  | 2.7–16 s                                  |
|                                   | Scanning ceph  | 6.4-9.9 s                                 |
|                                   | ProCeph  | 0.1-0.8 s                                 |
|                                   | Tomo   | 3 s / frame                               |
| SID                               | Pan  | 500 mm (19 in.)                           |
|                                   | Ceph   | 170 cm (67 in.)                           |
| Magnification                     | Pan  | constant 1.2                              |
|                                   | Ceph   | 1.08-1.13                                 |
| CCD pixel size                    | 48 μm  |   |
| Image pixel size                  | 48/96/144 μm selectable                                      |   |
| CCD active surface                | Pan  | 6 x 147 mm                                |
|                                   | Ceph   | 6 x 295 mm                                |
| Resolution (digital)              | Pan  | max. 9 lp/mm                              |
|                                   | Ceph   | max. 5.7 lp/mm                            |
| Image field (digital)             | Pan  | 14 x 30 cm (5.5 x 12 in.)                 |
|                                   | Ceph   | 24/27 x 18/30 cm<br>(9/10.6 x 7/11.8 in.) |
| File size, uncompressed (digital) | Pan  | 4–33 MB                                   |
|                                   | Ceph   | 7–16 MB                                   |
| Line voltage                      | 100–240 V, 50 or 60 Hz                                       |   |
| Regulation                        | Automatic, ±10 %   |   |
| Line current                      | 8–16 A   |   |
| Colour                            | White (RAL 9016)   |   |

#### **Imaging programs**

|                                       | Planmeca ProMax 2D S3   | Planmeca ProMax 2D S2   |
|---------------------------------------|---|---|
| Standard: Basic panoramic programs    | Standard panoramic  | Standard panoramic  |
|                                       | Lateral TMJ (closed & open)   | Lateral TMJ (closed & open)   |
|                                       | PA TMJ (closed & open)  | PA TMJ (closed & open)  |
|                                       | PA sinus  | PA sinus  |
| Standard                              | Child (Paediatric) mode for each standard and optional program to reduce the dose | Child (Paediatric) mode for each standard and optional program to reduce the dose |
| Optional                              | Horizontal and vertical segmenting for panoramic program                          | Horizontal and vertical segmenting for panoramic program                          |
| Optional                              | True Bitewing   | Bitewing  |
| Optional: Advanced panoramic programs | Interproximal panoramic   |   |
|                                       | Orthogonal (perio) panoramic  |   |
|                                       | Lateral-PA TMJ  |   |
|                                       | Lateral multiangle TMJ  |   |
|                                       | PA multiangle TMJ   |   |
|                                       | PA linear sinus   |   |
|                                       | Lateral sinus   |   |
| Optional: Tomography programs         | Digital linear tomography   |   |

#### **Dimensions**





## **Physical space requirements**

|         | Planmeca ProMax 2D     | Planmeca ProMax 2D with cephalostat |
|---------|------------------------|-------------------------------------|
| Width   | 100 cm (39.4 in.)      | 202 cm (79.5 in.)                   |
| Depth   | 125 cm (49 in.)        | 125 cm (49 in.)                     |
| Height* | 156–234 cm (61–92 in.) | 156-234 cm (61-92 in.)              |
| Weight  | 113 kg (lbs 248)       | 128 kg (lbs 282)                    |

 $<sup>\</sup>hbox{\rm *The maximum height of the unit can be adjusted for offices with limited ceiling space.}$ 

## Stand out with colour



## Planmeca ProOne®

# **Technical specifications**

#### **Technical data**

| Generator        | Constant potential, resonance mode high frequency 60–80 kHz |
|------------------|---|
| X-ray tube       | D-058SBR  |
| Focal spot size  | 0.5 x 0.5 mm (IEC 336)                                      |
| SID              | 480 mm (19 in.)   |
| Total filtration | min. 2.5 mm Al eq.  |
| Anode voltage    | 60-70 kV  |
| Anode current    | 2–7 mA DC   |
| Exposure time    | 2–10 s  |
| Line voltage     | 100-132 V~ 50/60 Hz, 180-240 V~ 50 Hz                       |
| Regulation       | ±10 % (automatic)   |
| Line current     | 8–16 A  |
| Power uptake     | max: 850 W  |
| Chin rest level  | 95–178 cm (37.4–70 in.)                                     |
| Colour           | White (RAL 9016)  |


#### **Imaging programs**


| Standard: Basic panoramic programs | Standard panoramic  |
|------------------------------------|---|
|                                    | Lateral TMJ   |
|                                    | PA TMJ  |
|                                    | PA Sinus  |
| Standard                           | Child (Paediatric) mode for each program to reduce the dose |
| Optional                           | Horizontal and vertical segmenting for panoramic program    |
| Optional                           | Bitewing  |
| Optional: Advanced                 | Interproximal panoramic                                     |
| panoramic programs                 | Orthogonal (perio) panoramic                                |
|                                    | Lateral-PA TMJ  |
|                                    | Lateral multiangle TMJ                                      |
|                                    | Lateral non rotational sinus                                |
|                                    | Cross-sections  |
|                                    | Bitewing  |

#### Physical space requirements

| Width  | 97 cm (38 in.)  |
|--------|-----------------|
| Depth  | 103 cm (41 in.) |
| Height | 223 cm (88 in.) |
| Weight | 67 kg (148 lbs) |

#### **Dimensions**






## Planmeca ProX™

# Technical specifications


#### **Technical data**

| Generator                                       | Constant potential, microprocessor controlled, operating frequency 66 kHz                                   |
|---|---|
| X-ray tube                                      | Toshiba D-041SB   |
| Focal spot size                                 | 0.4 mm according to IEC 60336   |
| Cone diameter                                   | 60 mm (2.36 in.) Rectangular 36 x 45 mm (1.42 x 1.77 in.)   |
| Max. symmetrical radiation field                | Ø60 mm at SSD 200 mm Ø60 mm at SSD 300 mm according to IEC 806  |
| Total filtration                                | min. 2.5 mm Al equivalent at 70 kV according to IEC 60522   |
| Inherent filtration                             | 1 mm Al equivalent at 70 kV according to IEC 60522  |
| Anode voltage                                   | 60, 63, 66, 70 kV   |
| Anode current                                   | 8, 7, 6, 5, 4, 3, 2 mA  |
| Exposure times                                  | 0.01–2 sec., 24 steps   |
| SSD (Source-Skin<br>Distance) Standard/<br>Long | 200 mm (8 in.)/300 mm (12 in.)  |
| Mains voltage                                   | 100 V~/110-115 V~/220-240 V~, 50/60 Hz  |
| Duty cycle                                      | 1:13.5  |
| Electrical classification                       | Class I Type B  |
| Weight  | total 29 kg (64 lbs) tube head with standard cone 4.2 kg (9.3 lbs) tube head with long cone 4.5 kg (10 lbs) |
| Colour  | White (RAL 9016)  |

#### **Dimensions**



#### **Installation options**



## Planmeca ProSensor® HD

# **Technical specifications**

|                          | Size 0                           | Size 1                           | Size 2                          |
|--------------------------|----------------------------------|----------------------------------|---------------------------------|
| Sensor size              | 33.6 x 23.4 mm (1.33 x 0.92 in.) | 39.7 x 25.1 mm (1.56 x 0.99 in.) | 44.1 x 30.4 mm (1.76 x 1.2 in.) |
| Active area              | 25.5 x 18.9 mm (1.0 x 0.74 in.)  | 30.6 x 20.7 mm (1.20 x 0.81 in.) | 36 x 26.1 mm (1.42 x 1.03 in.)  |
| Number of pixels, normal | 850 x 629 px                     | 1020 x 690 px                    | 1200 x 870 px                   |
| Number of pixels, high   | -                                | 2040 x 1380 px                   | 2400 x 1740 px                  |
| Pixel size, normal       | 30 μm x 30 μm                    |                                  |                                 |
| Pixel size, high         | 15 µm x 15 µm                    |                                  |                                 |
| Theoretical resolution   | 33 lp/mm                         |                                  |                                 |
| Resolution, normal       | 17 lp/mm                         |                                  |                                 |
| Resolution, high         | >20 lp/mm                        |                                  |                                 |
| Interface                | USB or Ethernet                  |                                  |                                 |
| View delay               | <5 sec.                          |                                  |                                 |







# Planmeca ProScanner® 2.0

# **Technical specifications**

| Imaging plate sizes         | 0, 1, 2                                  |
|-----------------------------|--|
| Pixel size                  | 30 μm                                    |
| True resolution             | 12 lp/mm                                 |
| Theorethical resolution     | 16.7 lp/mm                               |
| Bits per pixel / Gray scale | 16 bit / 65538                           |
| Weight                      | 4 kg (8.8 lbs)                           |
| Dimensions (H x W x D)      | 231 x 167 x 216 mm (9.1 x 6.6 x 8.5 in.) |
| Interfaces                  | Network                                  |
| Eraser                      | Embedded                                 |







## Planmeca Romexis®

# Technical specifications

| Supported 2D modalities                     | Intraoral  |
|---|--|
|   | Panoramic  |
|   | Cephalometric  |
|   | 2D linear tomography   |
|   | Photos   |
|   | Stack images (CBCT slices and panoramic slices)  |
| Supported 3D modalities                     | 3D CBCT  |
|   | 3D photo   |
|   | 3D surface scan  |
| Supported photo sources                     | Intraoral camera   |
|   | Digital camera or scanner (import or TWAIN capture)  |
| Operating systems                           | Win 7 Pro (64 bit) / Win 8.1 Pro (64 bit) / Win 10 Pro (64 bit)  |
|   | Win 2008 Server / Win 2012 Server  |
|   | Mac* (OS X or newer)   |
|   | For detailed information please see system   |
|   | requirements of Planmeca Romexis www.planmeca.com  |
|   | *Cephalometric Analysis module, 3D Ortho Studio module<br>and Planmeca PlanCAD Easy are supported on Windows<br>operating systems. |
| Image formats                               | JPEG or TIFF (2D images)   |
|   | DICOM (2D and 3D images)   |
|   | STL, OBJ, PLY (3D surface models)  |
|   | TIFF, JPEG, PNG, BMP (imports/exports)   |
| Image size                                  | 2D X-ray image: 1–9 MB   |
|   | 3D X-ray image: typically 50 MB–1 GB   |
| Installation options                        | Client–Server  |
|   | Java Web Start deployment  |
| DICOM 3.0 support                           | DICOM Import/Export  |
|   | DICOM DIR Media Storage  |
|   | DICOM Print SCU  |
|   | DICOM Storage SCU  |
|   | DICOM Storage SCP  |
|   | DICOM Worklist SCU   |
|   | DICOM Query/Retrieve   |
|   | DICOM Storage Commitment   |
|   | DICOM MPPS   |
|   | TWAIN Client   |
|   |  |
|   | PMBridge (patient information and images)  VDDS (patient information and images)   |
|   | "  |
|   | InfoCarrier (patient information)  |
| 3 <sup>rd</sup> party software integrations | Dolphin Imaging  |
|   | NobelClinician   |
|   | Simplant   |
|   | Straumann coDiagnostiX   |
|   | _  |
|   | Cybermed N-Liten   |
|   | Cybermed N-Liten 3D Diagnostics service 360imaging service   |

#### Find all the latest Planmeca news



www.facebook.com/PlanmecaOy



www.nlanmeca.com/newsroom



Planmeca Oy designs and manufactures a full line of industry-leading dental equipment, including 3D and 2D imaging devices, CAD/CAM solutions, dental care units and software. Planmeca Oy, the parent company of the Finnish Planmeca Group, is strongly committed to better care through innovation, and it is the largest privately held company in the field.

Follow us on social media!



### **PLANMECA**

Asentajankatu 6 | 00880 Helsinki | Finland | tel. +358 20 7795 500 | fax +358 20 7795 555 | sales@planmeca.com | www.planmeca.com

Images may contain optional items not included in standard delivery. Available configurations and features may have country or area specific variations.