

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name:	Maxima Oil Spray
Supplier:	Henry Schein
SDS:	1 November 2026
Supplier Details:	Henry Schein New Zealand 243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745 Ph. 0800 808 855 www.henryschein.co.nz
Emergency Contacts:	Poisons/Hazardous Chemical Info Centre – 0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police
HSNO Class/Category:	2/6
HSNO Group Standard:	Aerosols Flammable Group Standard 2020 HSR002515
Statements/Pictograms:	As per attached Safety Data Sheet (SDS)
Date Prepared:	This coversheet was prepared – January 2024

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.

## Henry Schein Maxima HP Spray

Part No. P10577CT-A (Aerosol) Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 1/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

L.1	Product Ide	entifier		. 11ann. Calaire		
Product	: Name cturer Product N	lumber		: Henry Schein Ma : P10577CT-A	axima HP Spray	
vianura				.110377CT-A		
.2	Other Mea	ns of Ide	ntification			
Other Id	lentifiers			: Not Available		
3	Relevant Io	dentified	Uses of the Su	bstance or Mi	xture and Uses Advised A	gainst
ecomn	nended Use			: Dental Lubrican	t	
estricti	ions on Use			: None Identified		
L <b>.4</b>	Supplier D	etails				
					Manufacturer Details	Supplier Details
-	ny Name					Properpak
ddress	5					P.O. Box 11157, Bainbridge, WA 98110 - United
						States
	Number					206-321-2589
ax Nun	nder					
imail Vebsite	_					
vebsite	e					
.5	24 hr Emer	gency Ph	one Number			
		0				
	ncy Number ION 2 - HAZ		DENTIFICATI	: 800-255-3924 Chem-Tel ON		
SECTI	ION 2 - HAZ	ARDS II		Chem-Tel		
SECTI 2.1 Flam. Ad	ION 2 - HAZ Classificati erosol 1	CARDS II on of the H222	DENTIFICATI Substance or Physical Hazards	Chem-Tel ON Mixture	Flammable aerosol Category 1	
SECTI 2.1 Flam. Ad Press. G	ION 2 - HAZ Classificati erosol 1 Sas (Comp.)	ARDS II on of the H222 H280	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture	Gases under pressure Compres	
SECTI 2.1 Flam. Ad Press. G	ION 2 - HAZ Classificati erosol 1 Sas (Comp.)	CARDS II on of the H222	DENTIFICATI Substance or Physical Hazards	Chem-Tel ON Mixture		
SECII 2.1 Flam. Ad Press. G Asp. Tox 2.2	ION 2 - HAZ Classificati erosol 1 ias (Comp.) x. 1 Label Elem	ARDS II on of the H222 H280 H304	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture	Gases under pressure Compres	
SECII 2.1 Flam. Ad Press. G Asp. Tox 2.2	ION 2 - HAZ Classificati erosol 1 Eas (Comp.) x. 1	ARDS II on of the H222 H280 H304	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture	Gases under pressure Compres	
SECII 2.1 Flam. Ad Press. G Asp. Tox 2.2	Classificati erosol 1 fas (Comp.) x. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel	Gases under pressure Compress Aspiration hazard Category 1	
SECTI Flam. Ad Press. G Asp. Tox 2.2 Hazard I	Classificati erosol 1 fas (Comp.) x. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture	Gases under pressure Compress Aspiration hazard Category 1	ssed gas
2.1 Flam. Ad Press. G Asp. Tox 2.2 Hazard I	ION 2 - HAZ Classificati erosol 1 Gas (Comp.) X. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Gases under pressure Compress Aspiration hazard Category 1	ssed gas
2.1 Flam. Ad Press. G Asp. Tox 2.2 Hazard I	ION 2 - HAZ Classificati erosol 1 Gas (Comp.) X. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture	Gases under pressure Compress Aspiration hazard Category 1	rrosol sure; may explode if heated
SECT Flam. Ad Press. G Asp. Tox 2.2 Hazard I Hazard I	ION 2 - HAZ Classificati erosol 1 Gas (Comp.) X. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304 ents	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture  G G G G G G G G G G G G G G G G G G	Gases under pressure Compress Aspiration hazard Category 1 GHS04	ssed gas
SECTI 2.1 Flam. Ad Press. G Asp. Tox 2.2 Hazard I Hazard I	ION 2 - HAZ Classificati erosol 1 ias (Comp.) x. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304 ents	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture 5 5 5 5 5 5 5 5 5 5 5 5 5	Gases under pressure Compress Aspiration hazard Category 1 GHS04	ssed gas
SECTI 2.1 Flam. Ad Press. G Asp. Tox 2.2 Hazard I Hazard I	ION 2 - HAZ Classificati erosol 1 ias (Comp.) x. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304 ents	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture 5 5 5 5 5 5 5 5 5 5 5 5 5	Gases under pressure Compress Aspiration hazard Category 1 GHS04	ssed gas
2.1 Elam. Ad Press. G Asp. Tox 2.2 Hazard I Hazard S	ION 2 - HAZ Classificati erosol 1 ias (Comp.) x. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304 ents	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture 5 5 5 5 5 5 5 5 5 5 5 5 5	Gases under pressure Compress Aspiration hazard Category 1	ssed gas prosol sure; may explode if heated ed and enters airways ot surfaces, sparks, open flames and other ignition sources. In flame or other ignition source. In on ot pierce or burn, even after use. ely call a POISON CENTER.
SECTI Flam. Ad Press. G Asp. Tox 2.2 Hazard I Hazard I	ION 2 - HAZ Classificati erosol 1 ias (Comp.) x. 1 Label Elem Pictograms	ARDS II on of the H222 H280 H304 ents	DENTIFICATI Substance or Physical Hazards Physical Hazards	Chem-Tel ON Mixture 5 5 5 5 5 5 5 5 5 5 5 5 5	Gases under pressure Compress Aspiration hazard Category 1 GHS04	ssed gas prosol sure; may explode if heated ed and enters airways ot surfaces, sparks, open flames and other ignition sources. In flame or other ignition source. In on ot pierce or burn, even after use. ely call a POISON CENTER. I.

## Henry Schein Maxima HP Spray

Part No. P10577CT-A (Aerosol) Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 2/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### P501

: None Identified.

: Dispose of contents/container to applicable regulations.

#### 2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified

#### 2.4 Unknown acute toxicity

50% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 50% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

### **SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

#### 3.1 Substance / Mixture

Substance / Mixture

: Mixture

3.2 Composition		
Substance name	CAS Number % wt* Classi	ification
White Mineral Oil	8042-47-5 30 - 60 Asp. 7	Гох. 1, Н304
Propane		Gas 1, H220 . Gas (Diss.), H280
N-Butane		Gas 1, H220 . Gas (Diss.), H280
Isobutane		Gas 1, H220 . Gas (Diss.), H280
Full text of hazard classes and H-statements : see section 16	*Chemical name_CAS number and/or exact co	ncentration have been withheld as a trade secre

### **SECTION 4 - FIRST-AID MEASURES**

4.1 Description of First-Aid N	leasures
General Measures	: Call a physician immediately.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
Skin Contact	: Wash skin with plenty of water.
Eye Contact	: Rinse eyes with water as a precaution.
Ingestion	: Do NOT induce vomiting. Call a physician immediately.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.
4.2 Most Important Sympton	ns and Effects, Both Acute and Delayed
Symptoms of Exposure	: Confusion, Dizziness, Narcosis, Drowsiness, Diarrhea.
Delayed Effects	: No known delayed effects.
Immediate Effects	: Aspiration hazard.

#### 4.3 Indication of Immediate Medical Attention and Special Treatment Notes to Physician : Treat symptomatically. Specific Treatments/Antidotes : No Information Available. : May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

: No known chronic effects.

: Central Nervous System.

# **Medical Conditions Aggravated**

**SECTION 5 - FIRE-FIGHTING MEASURES** 

#### **Suitable Extinguishing Media** 5.1

**Extinguishing Media Unsuitable Media** 

**Chronic Effects** 

**Target Organs** 

: Water, carbon dioxide, dry chemical, universal aqueous film forming foam. : Water jet.

# Henry Schein Maxima HP Spray

Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 3/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardo	ous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific	Hazards During Firefighting	: CONTENTS EXTREMELY FLAMABLE UNDER PRESSSURE. In a fire or if heated, a pressure increase willoccur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.
5.3	Special Protective Actions f	or Fire-Fighters
Firefigh	iting Instructions	: Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
Protect	ion during Firefighting	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.
SECT	ION 6 - ACCIDENTAL RELE	ASE MEASURES
6.1	Personal Precautions, Prote	ective Equipment and Emergency Procedures
For Non	-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Eme	ergency Personnel	: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.
6.2	<b>Environmental Precautions</b>	
Enviror	nmental Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to preventenvironmental contamination.
6.3	Methods and Materials for	Containment and Cleaning up
Contain	ment Procedures	: Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
Cleanup	Procedures	: Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Ir	nformation	: Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
Prohibit	ed Materials	: Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.
SECT	ION 7 - HANDLING AND S	TORAGE
7.1	Precautions for Safe Handli	ng
General	Handling Precautions	: KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
Hygiene	Recommendations	: Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.
7.2	Conditions for Safe Storage	Including Any Incompatibilities
Storage	Requirements	: Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
Incomp	atibilities	: Segregate storage away from materials indicated in Section 10.
	DB Classification	: This product is classified as a Level 3 Aerosol per NFPA 30B

### Henry Schein Maxima HP Spray

Part No. P10577CT-A (Aerosol) Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 4/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### 8.1 **Control Parameters**

o.i Control Paramete	15	
N-Butane (106-97-8)		
ACGIH	ACGIH OEL TWA	1000 ppm
ACGIH	ACGIH OEL Ceiling	1000 ppm
DSHA	OSHA PEL (TWA) [2]	800 ppm
liosh	NIOSH REL (TWA)	1900
NIOSH	NIOSH REL TWA [ppm]	800 ppm
California	California PEL (TWA) (mg/m3)	1900 mg/m³
California	California PEL (TWA) (ppm)	800 ppm
Propane (74-98-6)		
DSHA	OSHA PEL (TWA) [1]	1800 mg/m³
OSHA	OSHA PEL (TWA) [2]	1000 ppm
NIOSH	IDLH [ppm]	2100 ppm
liosh	NIOSH REL (TWA)	1800 mg/m³
NIOSH	NIOSH REL TWA [ppm]	1000 ppm
California	California PEL (TWA) (mg/m3)	1800 mg/m³
California	California PEL (TWA) (ppm)	1000 ppm
sobutane (75-28-5)		
ACGIH	ACGIH OEL TWA	1000 ppm
liosh	NIOSH REL (TWA)	1900 mg/m <sup>3</sup>
NIOSH	NIOSH REL TWA [ppm]	800 ppm
White Mineral Oil (8042-47-5)		
ACGIH	ACGIH OEL TWA [ppm]	5 mg/m³ Oil Mist
OSHA	OSHA PEL (TWA) [1]	5 mg/m³ Oil Mist
NIOSH	NIOSH REL (TWA)	5 mg/m³ Oil Mist
NIOSH	NIOSH REL (STEL)	10 mg/m³ Oil Mist
California	California PEL (TWA) (mg/m3)	5 mg/m <sup>3</sup>
.2 Exposure Controls		
ngineering Measures	: Use only with adequate ventilation. General ventilation	(typically 10 air changes per hour) should be used.
- •	Ventilation rates should be matched to conditions. Loc	
	may be necessary to control air contamination below t	hat of the lowest OEL from the table above.
ersonal Protective Equipment		
Eye / Face Protection	: Safety glasses with side shields are recommended as a n Where eye contact with this material could occur, chen	
Hand Protection	: Chemical-resistant gloves, tested according to ASTMF90	)3-17.
Remarks	: Choose gloves to protect hands against chemicals depen hazardous substance and specific to the place of work.	

**Skin and Body Protection** 

**Respiratory Protection** 

Compliance **Other Protective Equipment** 

- hazardous substance and specific to the place of work.
- : For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
- : An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.
- : If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.
- : Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

**Environmental Exposure Controls** 

: Avoid release to the environment.

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

9.1 Physical Properties			
Boiling Point	230.00 °C	Melting / Freezing Point	Not Available
Flash Point, Liquid	> 93.40 °C	Flash Point, Propellant	> -104.44 °C

#### Part No. P10577CT-A (Aerosol)

## Henry Schein Maxima HP Spray

Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 5/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosive Limits	LEL: n/a UEL: 1.00 vol %	Autoignition Temperature, Liquid	371.00 °C
Flammability	Extremely Flammable Aerosol	Density	0.649 g/cm³
Molecular Weight	Not Available	Weight	5.416 lbs/gal
Vapor Pressure	Not Available	рН	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAc=1)	Not Available
Viscosity	17.25 cSt (centistoke)	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Pressurized Product	Heat Of Combustion	> 18829.71 BTU/lb
Appearance / Color	Colorless	Water Solubility	Not Available
Odor	Slight	Decomposition Temperature	Not Available
9.2 Environmental Pro	operties		
Percent Volatile	50.00 % wt	VOC Regulatory	324.36 g/L (2.71 lbs/gal)
Percent VOC	50.00 % wt	VOC Actual	324.50 g/L (2.71 lbs/gal)
Percent HAP	0.00 % wt	HAP Content	0.00 g/L (0.00 lbs/gal)
Global Warming Potential	1.57 GWP	Maximum Incremental Reactivity	0.4830 g O3/g
Ozone Depletion Potential	0.00 ODP		

### **SECTION 10 - STABILITY AND REACTIVITY**

#### 10.1 Reactivity

Reactivit	ty	: No specific test data related to reactivity is available for this products or its ingredients.
10.2	Chemical Stability	
Chemica	l Stability	: This product is stable.
10.3	Possibility of Hazardous Reactio	ns
Hazardo	us Reactions	: Under normal conditions of storage and use, hazardous reactions are not expected to occur.
10.4	Conditions to Avoid	
Conditio	ns to Avoid	: Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.
10.5	Incompatible Materials	
Materia	s to Avoid	: Strong Oxidizing Agents, Halogen Compounds.
10.6	Hazardous Decomposition Produ	ucts
Thermal	Decomposition	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Thermal Decomposition** 

SECTION 11 - TOXICOLOGICAL INFORMATION

#### 11.1 Information on Toxicological Effects

N-Butane (CAS: 106-97-8 / EC: 203-448-7)		
658 mg/l/4h (ChemInfo)		
276000 ppm/4h (ChemInfo)		
658 mg/l/4h (Lit.)		
Isobutane (CAS: 75-28-5 / EC: 200-857-2)		
368000 ppm/4h (ChemInfo)		
White Mineral Oil (CAS: 8042-47-5 / EC: 232-455-8)		
> 5000 mg/kg body weight (ChemInfo)		
> 2000 mg/kg body weight (ChemInfo)		

### Henry Schein Maxima HP Spray

Part No. P10577CT-A (Aerosol) Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0(EN)-US Page: 6/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Routes Of Exposure Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation. : See Section 4.2
Skin Corrosion/Irritation	: Not classified
Eye Damage/Irritation	: Not classified
Respiratory or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Not classified
STOT-Single Exposure	: Not classified
STOT-Repeated Exposure	: Not classified
Aspiration Hazard	: May be fatal if swallowed and enters airways.
Vaporizer	: Aerosol
Carcinogen Data	: None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

## **SECTION 12 - ECOLOGICAL INFORMATION**

### 12.1 Ecotoxicity and Ecological Properties

n-Butane (106-97-8)		
Persistence and Degradibility	Readily biodegradable in water.	
Bioconcentration Factor	33.52	
Log Pow	2.89	
Bioacculative Potential	Low potential for bioaccumulation (Log Kow < 4).	
Log Koc	1.641	
Propane (74-98-6)		
Persistence and Degradibility	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.	
BCF Fish	9 – 25 (BCF)	
Log Pow	2.28 (Calculated)	
Bioacculative Potential	Low potential for bioaccumulation (Log Kow < 4).	
Isobutane (75-28-5)		
Persistence and Degradibility	Readily biodegradable in water. Biodegradable in the soil. Not applicable (gas).	
BCF Fish	26.62	
Log Pow	2.76	
Bioacculative Potential	Low potential for bioaccumulation (BCF < 500).	
Log Koc	1.545	
White Mineral Oil (8042-47-5)		
LC50 Fish	> 100 mg/l Rainbow Trout - 96hr	
EC50 Daphnia	> 100 mg/l Water Flea - 48hr	
Persistence and Degradibility	Biodegradability 24% / 28 days.	
Log Pow	> 6 (Calculated)	
Bioacculative Potential	High potential for bioaccumulation (Log Kow > 5).	

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

13.1	Waste Treatment Methods	
Waste D	bisposal	: Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste D	Disposal Of Packaging	: In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.
Landfill	Precautions	: Not Available.

### Part No. P10577CT-A (Aerosol)

### Henry Schein Maxima HP Spray

Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 7/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Incineration Precautions** 

: \*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*.

### **SECTION 14 - TRANSPORTATION INFORMATION**

14.1	UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)	
UN Num	ber	: UN1950	UN1950	UN1950	
14.2	UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)	
UN Prop	er Shipping Name	Aerosols, Limited Quantit	y Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity	
14.3	Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)	
Transpor	t Hazard Class(es)	: 2.1	2.1	2.1	
Labels		: None	2.1 - Flammable gas	None	
Limited (	Quantity	: Yes	Yes	Yes	
EmS Code		: Not Applicable	Not Applicable	F-D, S-U	
14.4	Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)	
Packing (	Group	: None	None	None	
14.5	Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)	
Marine P	ollutant	: No	Νο	No	
14.6	Special Precautions				
Precautions		: None Identified			
14.7	Transport in Bulk				
Remarks		: Not applicable for product as su	pplied		
SECTI	ON 15 - REGULATORY INFO	RMATION			
15.1	Federal Regulations				
SARA Section 313       : This product or mixture is not known to contain a toxic chemical or chemicals in excess of the appi         minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of         of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.		orting requirements of section 31			
TSCA Section 12(b)		: This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D			
CERCLA F	Reportable Quantity	•	nown to contain a chemical or chemicals sul the Comprehensive Environmental Response	, , ,	

15.2	State	Regu	lations
------	-------	------	---------

**California Proposition 65** 

: This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### Part No. P10577CT-A (Aerosol)

### Henry Schein Maxima HP Spray

Print Date: 11/01/2021 Revision Date: 1/11/2021 Supersedes Date: 1/4/2021 Issue Date: 12/1/2020 Version: 3.0 (EN)-US Page: 8/8

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

State Right-to-Know Lists

: The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

n-Butane (106-97-8)	U.S New Jersey - Right to Know Hazardous Substance List
Propane (74-98-6)	U.S New Jersey - Right to Know Hazardous Substance List
Isobutane (75-28-5)	U.S New Jersey - Right to Know Hazardous Substance List

### **SECTION 16 - OTHER INFORMATION**

Indication of changes

:	Section	Changed item	Change
	1	Supersedes	Modified
	1	Revision date	Modified
	1	Name	Modified
	1	Product code	Modified

#### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.