

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: Die Spacer Conditioner & Thinner

Manufacturer: Henry Schein

SDS Expiry: 8 February 2028

Supplier Details: Henry Schein New Zealand
243-249 Bush Road, Rosedale, Auckland, 0632
PO Box 101 140, North Shore, Auckland 0745
Ph. 0800 808 855
www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –
0800POISON/0800764766 (24 Hours)
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6

HSNO Group Standard: Dental Products Flammable Group Standard 2020 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – February 2024

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name DVA DIE SPACER THINNER

Synonyms

1.2 Uses and uses advised against

Uses DENTAL RESTORATION • DENTISTRY

1.3 Details of the supplier of the product

Supplier name HENRY SCHEIN REGIONAL PTY LTD ATF HENRY SCHEIN REGIONAL TRUST

Address Building 3, Level 6, 189 O'Riordan St, Mascot, NSW, 2020, AUSTRALIA

Telephone 1300 658 822

Email customer.care@henryschein.com.au

Website <https://henryschein.com.au/>

1.4 Emergency telephone numbers

Emergency 13 11 26 (Poisons Information Centre)

1.7 Details of alternative suppliers of the product

Supplier name HENRY SCHEIN REGIONAL LTD

243-249 Bush Road, Rosedale, Auckland, 0632, NEW ZEALAND

Phone: 0800 808 855

Emergency: 0800 764 766 (National Poisons Centre)

info@henryschein.co.nz

<https://www.henryschein.co.nz>

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Flammable Liquids: Category 2

Health Hazards

Serious Eye Damage / Eye Irritation: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)

Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)

Repeated exposure may cause skin dryness or cracking.

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



PRODUCT NAME DVA DIE SPACER THINNER**Hazard statements**

AUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Prevention statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use appropriate media to extinguish.

Storage statements

P403 + P233 + P235	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P405	Store locked up.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (w/w)
METHYL ETHYL KETONE (2-BUTANONE)	78-93-3	201-159-0	100%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and normal washroom facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, etc when handling. Earth containers when dispensing fluids. Exposure to heat above 200°C may release methyl methacrylate monomer.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

- 2YE
- 2 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, fine water spray can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, preferably flammables store, removed from direct sunlight, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation and fire protection systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Methyl ethyl ketone (MEK)	SWA [AUS]	150	445	300	890
Methyl ethyl ketone (MEK)	SWA [Proposed]	200	590	300	885

PRODUCT NAME DVA DIE SPACER THINNER

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
METHYL ETHYL KETONE (2-BUTANONE)	ACGIH BEI	Methyl ethyl ketone in urine	End of shift	2 mg/L

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear barrier gloves.
Body	Wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If spraying, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	CLEAR COLOURLESS LIQUID
Odour	MILD KETONE ODOUR
Flammability	HIGHLY FLAMMABLE
Flash point	-4°C (cc)
Boiling point	79°C
Melting point	NOT AVAILABLE
Evaporation rate	6.0 (Butyl acetate = 1)
pH	NOT AVAILABLE
Vapour density	> 1 (Air = 1)
Relative density	0.86
Solubility (water)	SOLUBLE
Vapour pressure	83 mm Hg @ 24°C
Upper explosion limit	12.8 %
Lower explosion limit	2.6 %
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

9.2 Other information

VOC	860 g/L
------------	---------

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

PRODUCT NAME DVA DIE SPACER THINNER

10.4 Conditions to avoid

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
METHYL ETHYL KETONE (2-BUTANONE)	2737 mg/kg (rat)	6480 mg/kg (rabbit)	23500 mg/kg (rat)

Skin Contact may result in drying and defatting of the skin, rash and dermatitis.

Eye Causes serious eye irritation. Contact may result in irritation, lacrimation, pain and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Insufficient data available to classify as a mutagen.

Carcinogenicity Insufficient data available to classify as a carcinogen.

Reproductive Insufficient data available to classify as a reproductive toxin.

STOT - single exposure Over exposure may result in central nervous system (CNS) effects with headache, drowsiness and dizziness.

STOT - repeated exposure Repeated exposure to some solvents have been reported to cause adverse effects to the central nervous system (CNS), liver and kidney. Over exposure to methyl ethyl ketone (MEK) in combination with certain other solvents (eg n-hexane) may result in peripheral nerve damage.

Aspiration Aspiration into the lungs may result in chemical pneumonitis and pulmonary oedema.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

Methyl ethyl ketone (MEK) vapour in the atmosphere will degrade primarily by reaction with photochemically produced hydroxyl radicals. MEK is rapidly biodegradable.

12.3 Bioaccumulative potential

Methyl ethyl ketone (MEK) is not expected to bioaccumulate.

12.4 Mobility in soil

Methyl ethyl ketone (MEK) will volatilise from the soil and water surfaces and is highly mobile with in soil.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1193	1193	1193
14.2 Proper Shipping Name	ETHYL METHYL KETONE (METHYL ETHYL KETONE)	ETHYL METHYL KETONE (METHYL ETHYL KETONE)	ETHYL METHYL KETONE (METHYL ETHYL KETONE)
14.3 Transport hazard class	3	3	3
14.4 Packing Group	II	II	II

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code	●2YE
GTEPG	3A1
Specific EPG	3.0.021
EmS	F-E, S-D

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information	Original manufacturer details: Dental Ventures of America, Inc. 1787 Pomona Rd., Suite C Corona, 92880, CA, USA Phone: 951-270-0606
------------------------	---

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

SYNERGISM - ANTAGONISM: Ingredients in this product may act together to aggravate or reduce adverse effects. Accordingly the time weighted average concentration (TWA) provided for single ingredients should be considered as a guide only and all due care exercised when handling.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PRODUCT NAME DVA DIE SPACER THINNER**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name DVA DIE STONE CONDITIONER

Synonyms

1.2 Uses and uses advised against

Uses DENTAL RESTORATION • DENTISTRY

1.3 Details of the supplier of the product

Supplier name HENRY SCHEIN REGIONAL PTY LTD ATF HENRY SCHEIN REGIONAL TRUST

Address Building 3, Level 6, 189 O'Riordan St, Mascot, NSW, 2020, AUSTRALIA

Telephone 1300 658 822

Email customer.care@henryschein.com.au

Website <https://henryschein.com.au/>

1.4 Emergency telephone numbers

Emergency 13 11 26 (Poisons Information Centre)

1.7 Details of alternative suppliers of the product

Supplier name HENRY SCHEIN REGIONAL LTD

243-249 Bush Road, Rosedale, Auckland, 0632, NEW ZEALAND

Phone: 0800 808 855

Emergency: 0800 764 766 (National Poisons Centre)

info@henryschein.co.nz

<https://www.henryschein.co.nz>

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Flammable Liquids: Category 2

Health Hazards

Serious Eye Damage / Eye Irritation: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)

Specific Target Organ Toxicity (Single Exposure): Category 3 (Narcotic Effects)

Repeated exposure may cause skin dryness or cracking.

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word DANGER

Pictograms



PRODUCT NAME DVA DIE STONE CONDITIONER

Hazard statements

AUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Prevention statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use appropriate media to extinguish.

Storage statements

P403 + P233 + P235	Store in a well-ventilated place. Keep cool. Keep container tightly closed.
P405	Store locked up.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content (w/w)
METHYL ETHYL KETONE (2-BUTANONE)	78-93-3	201-159-0	>70%
2-PROPENOIC ACID POLYMER	25086-15-1	607-538-0	10 to 25%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and normal washroom facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, etc when handling. Earth containers when dispensing fluids. Exposure to heat above 200°C may release methyl methacrylate monomer.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

- 2YE
- 2 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, fine water spray can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, preferably flammables store, removed from direct sunlight, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation and fire protection systems.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Methyl ethyl ketone (MEK)	SWA [AUS]	150	445	300	890
Methyl ethyl ketone (MEK)	SWA [Proposed]	200	590	300	885

PRODUCT NAME DVA DIE STONE CONDITIONER

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
METHYL ETHYL KETONE (2-BUTANONE)	ACGIH BEI	Methyl ethyl ketone in urine	End of shift	2 mg/L

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear barrier gloves.
Body	Wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If spraying, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	CLEAR COLOURLESS LIQUID
Odour	MILD ODOUR
Flammability	HIGHLY FLAMMABLE
Flash point	-4°C (cc)
Boiling point	79.4°C (Approximately)
Melting point	NOT AVAILABLE
Evaporation rate	6.0 (Butyl acetate = 1)
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	0.86
Solubility (water)	SOLUBLE
Vapour pressure	83 kPa @ 24°C
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

PRODUCT NAME DVA DIE STONE CONDITIONER

10.4 Conditions to avoid

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), amines, alkanamines, aldehydes, chlorinated compounds, heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
METHYL ETHYL KETONE (2-BUTANONE)	2737 mg/kg (rat)	6480 mg/kg (rabbit)	23500 mg/kg (rat)

Skin Contact may result in drying and defatting of the skin, rash and dermatitis.

Eye Causes serious eye irritation. Contact may result in irritation, lacrimation, pain and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity Insufficient data available to classify as a mutagen.

Carcinogenicity Insufficient data available to classify as a carcinogen.

Reproductive Insufficient data available to classify as a reproductive toxin.

STOT - single exposure Over exposure may result in central nervous system (CNS) effects with headache, drowsiness and dizziness.

STOT - repeated exposure Repeated exposure to some solvents have been reported to cause adverse effects to the central nervous system (CNS), liver and kidney. Over exposure to methyl ethyl ketone (MEK) in combination with certain other solvents (eg n-hexane) may result in peripheral nerve damage.

Aspiration Aspiration into the lungs may result in chemical pneumonitis and pulmonary oedema.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

Methyl ethyl ketone (MEK) vapour in the atmosphere will degrade primarily by reaction with photochemically produced hydroxyl radicals. MEK is rapidly biodegradable.

12.3 Bioaccumulative potential

Methyl ethyl ketone (MEK) is not expected to bioaccumulate.

12.4 Mobility in soil

Methyl ethyl ketone (MEK) will volatilise from the soil and water surfaces and is highly mobile with in soil.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1193	1193	1193
14.2 Proper Shipping Name	ETHYL METHYL KETONE (METHYL ETHYL KETONE)	ETHYL METHYL KETONE (METHYL ETHYL KETONE)	ETHYL METHYL KETONE (METHYL ETHYL KETONE)
14.3 Transport hazard class	3	3	3
14.4 Packing Group	II	II	II

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code	●2YE
GTEPG	3A1
Specific EPG	3.0.021
EmS	F-E, S-D

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information Original manufacturer details:
Dental Ventures of America, Inc.
1787 Pomona Rd., Suite C
Corona, 92880, CA, USA
Phone: 951-270-0606

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

SYNERGISM - ANTAGONISM: Ingredients in this product may act together to aggravate or reduce adverse effects. Accordingly the time weighted average concentration (TWA) provided for single ingredients should be considered as a guide only and all due care exercised when handling.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PRODUCT NAME DVA DIE STONE CONDITIONER**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]