

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: Very Special Separator

Manufacturer: Dental Ventures of America, Inc.

SDS Expiry: 31 July 2028

Supplier Details: Henry Schein New Zealand
243-249 Bush Road, Rosedale, Auckland, 0632
PO Box 101 140, North Shore, Auckland 0745
Ph. 0800 808 855
www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –
0800POISON/0800764766 (24 Hours)
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6 / 9

HSNO Group Standard: Dental Products (Flammable) Group Standard 2020

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – October 2023

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.

Very Special Separator

1. PRODUCT AND COMPANY IDENTIFICATION

Date Revised: July, 2023
Supersedes: March, 2018

PRODUCT DESCRIPTION: Mold release

MANUFACTURER

Dental Ventures of America, Inc.
1787 Pomona Rd., Suite C
Corona, 92878, CA.

Emergency Contact: Infotrack: 800.535.5053

Emergency Phone: 951.270.0606

Alternative Emergency Phone: 800.228.6696

USE OR APPLICATION: Industrial mold release supplied exclusively for workplace use.

2. HAZARD(S) IDENTIFICATION

GHS CLASSIFICATIONS

SIGNAL WORD: Danger

GHS LABEL ELEMENTS

Flammable



Health



Irritant



Environment



HAZARD STATEMENTS

H225: Highly flammable liquid and vapor.

H315.H320: Causes skin and eye irritation.

H304: May be fatal if swallowed and enters airways.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces - no smoking.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P270: Do not eat, drink or smoke when using this product.

P281: Use personal protective equipment as required.

P285: In case of inadequate ventilation wear respiratory protection.

P273: Avoid release to the environment.

DESCRIPTION OF ANY HAZARDS NOT OTHERWISE CLASSIFIED: Data not available.

SAFETY DATA SHEET

VERY SPECIAL SEPARATOR

3. COMPOSITION /INFORMATION ON INGREDIENTS

Under GHS-OSHA 4.11 the precise composition of this product is withheld as confidential business information (CBI). A more complete disclosure can be provided to a health, or safety professional when necessary.

SUBSTANCES or MIXTURE: Mixture

NO.	COMPONENT	CAS.NO	PERCENT
1	Naphtha (Petroleum), light aliphatic	64742-49-0	< 100%
2	n-Hexane	110-54-3	< 50%
3	Cyclohexane	110-82-7	< 10%
4	Stoddard solvent	8052-41-3	< 2.5%
5	Trimethylsilica	68988-56-7	< 2.2%
6.	Xylene	1330-2-7	< 0.8%
7.	Psuedocumene	95-63-6	< 0.1%

4. FIRST-AID MEASURES

EYES: Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area immediately with large amounts of soap and water. Remove and wash contaminated clothing before reuse. Contact a physician if irritation occurs.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention.

INGESTION: Do not induce vomiting. Give large quantities of water. Call a physician immediately. Never give anything to by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

FLASH POINT: -25 F (for product or lowest flash point ingredient)

FLAMMABILITY: Extremely flammable class (1A)

EXTINGUISHING MEDIA: Water fog, dry chemical, carbon dioxide, or foam.

NOTE: Either atmosphere-supply or air-purifying respirators should be available for fire fighters (20 CFR 1819 134)

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Avoid contact with material. Persons not wearing proper protective equipment (See Section 8) should be excluded from the area until clean up is complete.

PROTECTIVE EQUIPMENT: See Section 8.

METHODS AND MATERIALS FOR CONTAINMENT: Dike area to prevent spill spreading and scoop up excess to recovery containers. Absorb remnant on noncombustible material such as clay and shovel into containers for disposal.

CLEANUP PROCEDURES: Dispose of any waste(s) generated in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Avoid skin and eye contact.

Avoid breathing vapor, mist or fumes.

Ensure that all containers are properly labeled to prevent accidental ingestion or improper disposal.

Reseal partly used containers.

Wash with soap and water before eating, drinking or using toilet facilities.

Store under cool, dry conditions and away from open flames and high temperatures.

Observe conditions of good industrial hygiene and safe working practice.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT: Clean, body covering clothing and footwear.

EYES AND FACE: Splash proof goggles or safety glasses with side shields.

SKIN: Impervious gloves, neoprene or nitrile rubber gloves.

VENTILATION: Should be sufficient to control any dust, mist, vapor or fumes produced by processing or handling method, breathing of vapor must be avoided.

RESPIRATORY: Not normally necessary unless the material is being used in such a way as to produce dust, mist, vapor, fumes or smoke, in which case NIOSH approved respiratory protection should be used. Ventilation should be sufficient to control any dust, mist, vapor or fumes produced by processing or handling method. Breathing of vapor must be avoided.

WORK HYGIENIC PRACTICES: Standard work place practices.

OTHER USE PRECAUTIONS: None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Hydrocarbon

APPEARANCE: Clear or blue

pH: Neutral

SP.GR: 0.70

DENSITY: 5.8 lbs./gal

VAPOR PRESSURE: N.A.

VISCOSITY ASPIRATION: N.A.

Note: Other properties are either not available, or do not apply.

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions. Unstable at elevated temperatures

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, and other unknown organic compounds

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong Lewis or mineral acids and strong mineral and organic bases.

SAFETY DATA SHEET

VERY SPECIAL SEPARATOR

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

Eyes: Liquid, vapors and mist are irritating and can cause a stinging sensation, tearing, reddening and swelling of the eyes.

Skin: Moderately irritating and may cause skin de fatting or sensitization.

Inhalation: Can cause nasal and respiratory irritation, CNS effects including fatigue, nausea, headache, unconsciousness and even death.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause fatal chemical pneumonitis.

CHRONIC EFFECTS:

Exposure may damage peripheral nerve tissue & result in peripheral neuropathy, may cause kidney damage or CNS effects. Pre-existing disorders may also be aggravated by exposure.

NUMERICAL MEASUREMENTS OF TOXICITY: Data not available.

12. ECOLOGICAL INFORMATION

EXOTOXICITY EFFECTS:

AQUATIC TOXICITY: No data is available on the product itself.

TOXICITY TO OTHER ORGANISMS: No data is available on the product itself.

PERSISTENCE AND DEGRADABILITY:

MOBILITY: No data is available on the product itself.

BIOACCUMULATION: No data is available on the product itself.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of waste in accordance with all federal, state and local regulations.

CONTAINER DISPOSAL METHOD: Since emptied containers retain product residue, all labeled hazard pre cautions must be observed. Consult with federal, state and local authorities for definitions of 'empty' and proper disposal practices.

SPECIAL PRECAUTIONS: Please refer to Section 8 for Exposure Controls/Personal Protection.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR) & International Air Transportation (ICAO/IATA)

UN Number:	UN1866	
UN Proper Shipping Name:	Resin solution	Contains: Naphtha, light aliphatic
Transport Hazard Class:	3	
Packing Group Number:	III	
Guidance on bulk transportation:	Unknown	
Special Precautions:	Unknown	

Water Transportation (IMO/IMDG)

UN Number:	UN1866	
Proper Shipping Name:	Resin Solution	Contains: Naphtha, light aliphatic
Hazard Class:	3	
Packaging Group:	III	
Marine Pollutant:	Yes	

SAFETY DATA SHEET

VERY SPECIAL SEPARATOR

International Air Transportation (ICAO/IATA)

UN Number	UN1866
Proper Shipping Name	Resin solution
Contains	Naphtha, Light Aliphatic
Hazard Class	3
Packaging Group	III

15. REGULATORY INFORMATION

A. Cal Safe Drinking Water & Toxic Enforcement Act of 1986

Chemical Name	Cas.No.	Cancer/Repro. Tox		Quantity
Ethyl Benzene	100-41-4	Yes	No	< 0.5%
Naphthalene	91-20-3	Yes	No	< 0.1%
Benzene	71-43-2	Yes	Yes	< 0.09%
Toluene	108-88-3	No	Yes	< 0.0003%

This product may contain traces of other Prop. 65 listed chemicals as impurities. However, any used as ingredients are listed above.



California Proposition 65: Warning: This product can expose you to chemicals including Toluene, which is known to the state of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov

B. CERCLA - 40 CFR 302.4

Releases exceeding the reportable quantity (RQ) must be reported to the national response center, (800) 424 8802. RQ for this product is 9.434 lbs. when based on its' (CAS 64742-49-0) content. (CAS 64742-49-0) can also be classified as an 'oil' and so releases may fall under the CERCLA petroleum exclusion and not reportable.

C. RCRA - 40 CFR 261.33

Product is a D001 ignitable liquid waste. The BDAT is incineration, fuels substitution or recover. No. 2 and No. 3 are RCRAU056 Hazardous waste.

D. SARA TITLE III- CFR 13378, CFR 21152

NO.	RQ (lbs.)	TPQ (lbs.)	SEC. 313	313 CAT.	311/312
(*1)		(*2)	(*3)	(*4)	(*5)

*1 = Reportable quantity of extremely hazardous substance, Sec. 302

*2 = Threshold planning quantity, extremely hazardous substance, Sec. 302

*3 = Toxic chemical Sec. 313 (individual chemical listed)

*4 = Toxic release inventory form category Sec. 313 (40 CFR 372.63 C)

*5 = Hazard category for SARA Sec. 311/312 reporting

H1 = Immediate (acute) health hazard

H2 = Delayed (chronic) health hazard

P3 = Fire hazard P4 = Sudden pressure release hazard P5 = Reactive Hazard

E. VOC - SCAQMD RULES

No.	Chemical	Quantity	VP mm Hg	gms./l.@20 C
1	Naphta, light aliphatic	<89%	125	623
4	Stoddard Solvent	<2.5%	2	20
6	Xylene	<1.0%	5.1	9

VERY SPECIAL SEPARATOR

F. INTERNATIONAL CHEMICAL INVENTORY STATUS:

EINECS-EU Listed, Exempted, Polymer substance, or as no longer polymer.
AICS-AUSTRALIA, ENCS-JAPAN, KECI/ECL-KOREA, IECSC/SEPA-CHINA, PICCS-PHILIPPINES,
DSL-CANADA, TSCA - USA: All components are listed or exempted.

G. WHMIS (CANADA)

WHMIS: D2B Materials causing other toxic effects - toxic material
WHMIS: B2 Flammable Liquids - Flash point of <37.8 C (100F)

16. OTHER INFORMATION

HMIS RATING:

HMIS III CODES:

Health: 2
Flammability: 3
Reactivity: 0

RATINGS:

0 = Minimal
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Personal protection rating to be supplied by user depending on conditions of use.

HAZARD CLASSIFICATIONS:

H225: Highly flammable liquid and vapor. (Flam.Liq. 2)
H304: May be fatal if swallowed and enters airways. (Asp.Tox 1)
H315: Causes skin irritation (Skin Irrit. 2)
H320: Causes eye irritation. (Eye Irrit. 2B)
H361: Suspected of damaging fertility or the unborn child. (Repr. 2)

DATE PREPARED: July 2023
SUPERSEDES: March 2018

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Dental Ventures of America, Inc. does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Further there are many international, federal, state and local laws and regulations governing chemical products and as it is beyond the scope of this SDS to determine which of these apply, it is the responsibility of the user to determine how these affect their use of the product.

- END OF SDS -