



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: Fuji COAT LC

Manufacturer: GC Corporation

SDS Expiry: 30 November 2025

Supplier Details: Henry Schein New Zealand

23 William Pickering Drive, Albany

PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6 / 9

HSNO Group Standard: Dental Products Flammable Group Standard 2017 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared on 8 January 2021

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: GC Fuji COAT LC
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet

Henry Schein Dental 23 William Pickering Drive, Albany Auckland 0632, NEW ZEALAND

PO Box 101140, NSMC Auckland 0745, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Acute Tox. 5 H333 May be harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child (causing atrophy of the testes).

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device. The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

(Contd. on page 2)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapour.

May be harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child (causing atrophy of the testes).

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves / eye protection / face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:			
CAS: 80-62-6	Methyl methacrylate	25-<50%	
EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Acute Tox. 5, H333		
	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	≥3-<5%	
EINECS: 278-355-8	Repr. 2, H361		
CAS: 128-37-0	Butylated hydroxytoluene	0.5-<1%	
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410		
	CAS: 80-62-6 EINECS: 201-297-1 CAS: 75980-60-8 EINECS: 278-355-8 CAS: 128-37-0	CAS: 80-62-6	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 2)

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

NIZ

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredient	· Ingredients with limit values that require monitoring at the workplace:				
80-62-6 Methyl methacrylate					
WES (New	Zealand)	Short-term value: 416 mg/m³, 100 ppm			
		Long-term value: 208 mg/m³, 50 ppm			
		skin			
IOELV (Eu	ropean Union)	Short-term value: 100 ppm			
		ong-term value: 50 ppm			
· DNELs					
80-62-6 M	80-62-6 Methyl methacrylate				
Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)			
Inhalative	DNEL inhalatio	on 208 mg/m3 (air) (worker, l. te., syst.)			
128-37-0 E	128-37-0 Butylated hydroxytoluene				
Dermal	DNEL dermal	0.5 mg/kg bw/day (man)			
Inhalative	DNEL inhalatio	on 3.5 mg/m3 (man)			

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

(Contd. on page 5)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 4)

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Light yellow
Odour: Ester-like
Odour threshold: Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 101 °C

· Flash point:

10 °C

· Flammability (solid, gas):

Not applicable.

· Ignition temperature:

Undetermined.

Decomposition temperature:

. . . .

· Auto-ignition temperature:

Not determined.

Time ignition temperature

· Explosive properties:

Product is not selfigniting.

Product does not present an explosion hazard.

· Explosion limits:

 Lower:
 2.1 Vol %

 Upper:
 12.5 Vol %

(Contd. on page 6)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

		(Contd. of page
· Vapour pressure:	Not determined.	
· Density:	Not determined.	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
VÕC (EC)	$0.0~\mathrm{g/l}$	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

Henre wan	city	
· LD/LC50	values rele	vant for classification:
80-62-6 M	ethyl meth	acrylate
Oral		6,000 mg/kg (rabbit)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))
128-37-0 I	Butylated h	ydroxytoluene
Oral	LD50	>6,000 mg/kg (rat (f+m)) (OECD 401)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

· Repeated dose toxicity No further relevant information available.

(Contd. on page 7)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 6)

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

Repr. 2

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · ADR, IMDG, IATA	UN1247
· UN proper shipping name · ADR	1247 METHYL METHACRYLATE MONOMER,
· IMDG, IATA	STABILIZED mixture METHYL METHACRYLATE MONOMER, STABILIZED mixture
	(Contd. on page 9)

(Contd. on page 8)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

	(Contd. of page
Transport hazard class(es)	
ADR	
8	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
Packing group ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-D
Stowage Category	B
Transport in bulk according to Annex II of Margand the IBC Code	pol Not applicable.
	Temperature control is not required, in regards to Specie
Transport/Additional information:	Provision 386. Product uses chemical stabilization.
ADR	IL
Limited quantities (LQ) Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Transport agragory	Maximum net quantity per outer packaging: 500 ml 2
Transport category Tunnel restriction code	2 D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1247, METHYL METHACRYLATE MONOMER STABILIZED mixture, 3, II

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 8)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· New Zealand Inventory of Chemicals		
80-62-6 Methyl methacrylate		
75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide		
10287-53-3 ethyl 4-dimethylaminobenzoate		
128-37-0 Butylated hydroxytoluene		

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02

GHS07 GH

- · **Signal word** Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

· Hazard statements

Highly flammable liquid and vapour.

May be harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child (causing atrophy of the testes).

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves / eye protection / face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 10)

Printing date 30.11.2020 Version number 2 Revision: 30.11.2020

Trade name: GC Fuji COAT LC

(Contd. of page 9)

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child (causing atrophy of the testes).

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 5: Acute toxicity - inhalation - Category 5 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category I

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.