



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: G-CEM ONE Adhesive Enhancing Primer

Manufacturer: GC Corporation

SDS Expiry: 18 July 2029

Supplier Details: Henry Schein New Zealand

243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 8 / 9

HSNO Group Standard: Dental Products Flammable Group Standard 2020 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – October 2025

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · **Details of the supplier of the safety data sheet** Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

· Further information obtainable from: Regulatory affairs

· Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flammable liquids Category 3 H226 Flammable liquid and vapour.

Skin corrosion Category 1A H314 Causes severe skin burns and eye damage.

Serious eye damage Category 1 H318 Causes serious eye damage.

Hazardous to the aquatic environment chronic Category 3H412 Harmful to aquatic life with long lasting effects.

- _____
- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- · Hazard statements

Flammable liquid and vapour.

Causes severe skin burns and eye damage.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

(Contd. on page 2)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 1)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 64-17-5	ethyl alcohol	25-<50%
EINECS: 200-578-6	Flammable liquids Category 2, H225	
CAS: 1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	≥10-<20%
EINECS: 217-388-4	Skin irritation Category 2, H315; Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H335	
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	5-<10%
	Skin irritation Category 2, H315; Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H335	
CAS: 128-37-0	Butylated hydroxytoluene	1-<2.5%
EINECS: 204-881-4	Hazardous to the aquatic environment acute Category 1, H400; Hazardous to the aquatic environment chronic Category 1, H410	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

(Contd. on page 3)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 2)

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:		
64-17-5 ethyl alcohol		
WES (New Zealand)	Short-term value: 1520 mg/m³, 800 ppm	
	Long-term value: 380 mg/m³, 200 ppm	
	oto	

· DNELs

128-37-0 Butylated hydroxytoluene

120-57-0 Butytatea nyaroxytotuene		
Dermal	DNEL dermal	0.5 mg/kg bw/day (man)
Inhalative	DNEL inhalation	3.5 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 4)

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Liquid

· Colour: According to product specification

· Odour: Alcohol-like · Odour threshold: Not determined.

• pH-value at 20 °C: 1.5

· Change in condition

• Melting point/freezing point: Undetermined.
• Initial boiling point and boiling range: Undetermined.
• Flash point: 30 °C
• Flammability (solid, gas): Flammable.

Auto-ignition temperature:
Undetermined.

Not determined.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
 Upper: Not determined.
 Vapour pressure: Not determined.
 Density at 20 °C: 0.98 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

• water: Fully miscible. • Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.
Kinematic: Not determined.

· Solvent content:

• Organic solvents: 31.0 %
 • Water: 35.0 %
 • VOC (EC) 462.4 g/l

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 5)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
64-17-5 ethyl alcohol			
Oral	LD50	7,060 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	20,000 mg/l (rat (f+m))	
128-37-0 Butylated hydroxytoluene			
Oral	LD50	>6,000 mg/kg (rat (f+m)) (OECD 401)	

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM_ONE_ADHESIVE_ENHANCING_PRIMER

(Contd. of page 6)

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

UN-Number	
NZS, IMDG, IATA	UN1993
UN proper shipping name	
NZS	1993 FLAMMABLE LIQUID, N.O.S. (ETHANG
IMPC LATA	SOLUTION)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ETHANOL SOLUTION)
Transport hazard class(es)	
NZS	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
NZS, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM_ONE_ADHESIVE_ENHANCING_PRIMER

	(Contd. of page
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
Transport in bulk according to Annex II of Mar	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
NZS	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
<i>IMDG</i>	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANG
	SOLUTION), 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· New Zealand Inventory of Chemicals		
7732-18-5	Water	
	ethyl alcohol	
1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	
	2-[(2-methyl-1-oxoallyl)oxy]ethyl 1,3-dihydro-1,3-dioxoisobenzofuran-5-carboxylate	
	Butylated hydroxytoluene	
3153-26-2	oxobis(pentane-2,4-dionato-O,O')vanadium	

· HSNO Approval numbers

64-17-5 ethyl alcohol

HSR001144

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

GHS05

- · Signal word Danger
- · Hazard statements

Flammable liquid and vapour.

(Contd. on page 9)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 8)

Causes severe skin burns and eye damage.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Oualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flammable liquids Category 2: Flammable liquids - Category 2

Flammable liquids Category 3: Flammable liquids - Category 3

Skin corrosion Category 1A: Skin corrosion/irritation - Category 1A

Skin irritation Category 2: Skin corrosion/irritation - Category 2

Serious eye damage Category 1: Serious eye damage/eye irritation – Category 1

Eye irritation Category 2: Serious eye damage/eye irritation - Category 2

Specific target organ toxicity - single exposure Category 3: Specific target organ toxicity (single exposure) - Category 3

Hazardous to the aquatic environment acute Category 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Hazardous to the aquatic environment chronic Category 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Hazardous to the aquatic environment chronic Category 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

(Contd. on page 10)

Printing date 18.07.2024 Version number 2 Revision: 18.07.2024

Trade name: G-CEM ONE ADHESIVE ENHANCING PRIMER

(Contd. of page 9)

- ·Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

NIZ