



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: G-Cem LinkForce Starter Kit – Paste A & B, G-Premio Bond &

G-Multi Primer

Manufacturer: GC Corporation

SDS Expiry: 2 November 2028

Supplier Details: Henry Schein New Zealand

243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6 / 8 / 9

HSNO Group Standard: Dental Products Flammable Group Standard 2020 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – May 2025

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: G-CEM_LinkForce_Paste_A_(Base)
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- $\cdot \textit{Details of the supplier of the safety data sheet}$

Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Lahel elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Urethane Dimethacrylate (UDMA)

· Hazard statements

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves.

If skin irritation or rash occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM LinkForce Paste A (Base)

(Contd. of page 1)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
	Urethane Dimethacrylate (UDMA)	10-<25%
EINECS: 276-957-5	Aquatic Chronic 2, H411; Skin Sens. 1, H317	
	2,2-dimethyl-1,3-propanediyl bismethacrylate	5-<10%
EINECS: 217-856-8	Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	titanium dioxide	0.5-<1%
EINECS: 236-675-5	Carc. 2, H351	
CAS: 3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol	0.5-<1%
EINECS: 221-359-1	Acute Tox. 3, H301; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water

(Contd. on page 3)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_A_(Base)

(Contd. of page 2)

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: Protect against electrostatic charges.
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

13463-67-7 titanium dioxide

WES (New Zealand) Long-term value: 10 mg/m³

· DNELs

13463-67-7 titanium dioxide

Inhalative DNEL inhalation 10 mg/m3 (man)

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM LinkForce Paste A (Base)

(Contd. of page 3)

- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Pasty · Colour: Yellow · Odour: Unpleasant · Odour threshold: Not determined. Not determined. · pH-value:

· Change in condition

· Melting point/freezing point: Undetermined. · Initial boiling point and boiling range: 190 °C

Not applicable. · Flash point: Not applicable. Flammability (solid, gas): Undetermined. · Auto-ignition temperature: Decomposition temperature: Not determined.

Product is not selfigniting. · Ignition temperature:

Product does not present an explosion hazard. • Explosive properties:

· Explosion limits:

· Lower: Not determined. · Upper: Not determined. · Vapour pressure: Not determined. · Density at 20 °C: 1.72 g/cm^3 Not determined. · Relative density Not determined. · Vapour density

(Contd. on page 5)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_A_(Base)

(Contd. of page 4)

• Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Insoluble.Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

· **VOC (EC)** 0.0 g/l

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
72869-86	72869-86-4 Urethane Dimethacrylate (UDMA)			
Oral	Oral LD50 >5,000 mg/kg (rat female) (OECD 401)			
13463-67	13463-67-7 titanium dioxide			
Oral	LD50	>5,000 mg/kg (mouse) (OECD 420)		
Inhalative	Inhalative LC50/4 h >6.82 mg/l (rat male)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

NI

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_A_(Base)

(Contd. of page 5)

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
NZS, ADN, IMDG, IATA	not regulated	
UN proper shipping name		
NZS, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
NZS, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
NZS, IMDG, IATA	not regulated	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex I	I of Marpol	
and the IBC Code	Not applicable.	

(Contd. on page 7)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_A_(Base)

(Contd. of page 6)

· UN "Model Regulation":

not regulated

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· New Zealan	· New Zealand Inventory of Chemicals		
65997-17-3	Glass, oxide, chemicals		
72869-86-4	Urethane Dimethacrylate (UDMA)		
1565-94-2	(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate		
1985-51-9	2,2-dimethyl-1,3-propanediyl bismethacrylate		
2530-85-0	3-trimethoxysilylpropyl methacrylate		
13463-67-7	titanium dioxide		
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol		
1309-48-4	magnesium oxide		
7631-86-9	silicon dioxide		
68909-20-6	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica		
10287-53-3	ethyl 4-dimethylaminobenzoate		
10373-78-1	Camphorquinone		
109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate		
1309-37-1	Iron(III)oxide		
20344-49-4	Iron hydroxide oxide		
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica		
1879-09-0	6-tert-butyl-2,4-xylenol		

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:

Urethane Dimethacrylate (UDMA)

· Hazard statements

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves.

If skin irritation or rash occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 8)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM LinkForce Paste A (Base)

(Contd. of page 7)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H301 Toxic if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.



Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: G-CEM LinkForce Paste B (Catalyst)
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet

Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the lung through prolonged or repeated exposure. Route of

exposure: Inhalation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labelling:

Urethane Dimethacrylate (UDMA)

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica

2,2'-ethylenedioxydiethyl dimethacrylate

· Hazard statements

Combustible liquid.

May cause an allergic skin reaction.

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM LinkForce Paste B (Catalyst)

(Contd. of page 1)

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous compone	ents:	
CAS: 72869-86-4	Urethane Dimethacrylate (UDMA)	10-<25%
EINECS: 276-957-5	Aquatic Chronic 2, H411; Skin Sens. 1, H317	
CAS: 109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate	5-<10%
EINECS: 203-652-6	Skin Sens. 1, H317	
CAS: 41637-38-1	Esterification products of 4,4'-isopropylidenediphenol, ethoxylated and 2-	5-<10%
	methylprop-2-enoic acid.	
	Aquatic Chronic 4, H413	
CAS: 94-36-0	Dibenzoyl peroxide	0.5-<1%
EINECS: 202-327-6	Org. Perox. B, H241; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 68909-20-6	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	1-<2.5%
EINECS: 272-697-1	STOT RE 2, H373	
CAS: 128-37-0	Butylated hydroxytoluene	0.1-<0.2%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM LinkForce Paste B (Catalyst)

(Contd. of page 2)

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: Protect against electrostatic charges.
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: None.

(Contd. on page 4)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_B_(Catalyst)

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

128-37-0 Butylated hydroxytoluene

Dermal	DNEL dermal	0.5 mg/kg bw/day (man)
Inhalative	DNEL inhalation	3.5 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · General Information
- · Appearance:

Form:
Pasty
Light beige
Odour:
Alcohol-like
Odour threshold:
Not determined.
Not determined.

(Contd. on page 5)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_B_(Catalyst)

(Contd. of page 4)

· Change in condition

• Melting point/freezing point: Undetermined. • Initial boiling point and boiling range: Undetermined.

· Flash point: 92 °C

Flammability (solid, gas):
 Auto-ignition temperature:
 Decomposition temperature:
 Not determined.

Not determined.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
 Upper: Not determined.
 Vapour pressure: Not determined.
 Density at 20 °C: 1.74 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

· water: Insoluble.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

 \cdot VOC (EC) 0.0 g/l

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

72869-86-4 Urethane Dimethacrylate (UDMA)

Oral LD50 >5,000 mg/kg (rat female) (OECD 401)

128-37-0 Butylated hydroxytoluene

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 6)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_B_(Catalyst)

(Contd. of page 5)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity May cause damage to organs through prolonged or repeated exposure.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

· Toxicity

· Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · NZS, IMDG, IATA

UN3082

(Contd. on page 7)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_B_(Catalyst)

	(Contd. of page
UN proper shipping name	
NZS IMDG	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Urethane Dimethacrylate (UDMA)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE
IATA	LIQUID, N.O.S. (Urethane Dimethacrylate (UDMA) Butylated hydroxytoluene), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Urethane Dimethacrylate (UDMA))
Transport hazard class(es)	
NZS	
Class Label	9 (M6) Miscellaneous dangerous substances and articles.
IMDG, IATA	
1 1 1 1 1 1 1 1 1 1	
Class Label	9 Miscellaneous dangerous substances and articles.9
Packing group NZS, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special marking (NZS):	Symbol (fish and tree) Symbol (fish and tree)
Special marking (NZS). Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
Transport in bulk according to Annex II of Marp and the IBC Code	p ol Not applicable.
Transport/Additional information:	
NZS	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM_LinkForce_Paste_B_(Catalyst)

(Contd. of page 7)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (URETHANE DIMETHACRYLATE (UDMA)), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · New Zealand Inventory of Chemicals

All ingredients are listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labelling:

Urethane Dimethacrylate (UDMA)

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica

2,2'-ethylenedioxydiethyl dimethacrylate

· Hazard statements

Combustible liquid.

May cause an allergic skin reaction.

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H241 Heating may cause a fire or explosion.

(Contd. on page 9)

Printing date 01.12.2023 Version number 2 Revision: 01.12.2023

Trade name: G-CEM LinkForce Paste B (Catalyst)

(Contd. of page 8)

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Regulatory affairs

· Contact: msds@gc.dental

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 4: Flammable liquids - Category 4

Org. Perox. B: Organic peroxides – Type B

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.



Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: G-Premio BOND
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- Details of the supplier of the safety data sheet Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

· Further information obtainable from: Regulatory affairs

· Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms









GHS02

2 GHS05

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

2,2'-ethylenedioxydiethyl dimethacrylate

 $diphenyl (2,4,6-trimethylbenzoyl) phosphine\ oxide$

· Hazard statements

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

(Contd. on page 2)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio BOND

(Contd. of page 1)

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1
CAS: 1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	≥10-<20%
EINECS: 217-388-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	5-<10%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1
CAS: 109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate	2.5-<5%
EINECS: 203-652-6	Skin Sens. 1, H317	1
CAS: 75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	1-<2.5%
EINECS: 278-355-8	Repr. 2, H361	1
CAS: 128-37-0	Butylated hydroxytoluene	≥0.25-<0.5%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio BOND

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eve contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

ΝZ

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio BOND

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:		
67-64-1 acetone		
WES (New Zealand)	Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm bio	
IOELV (European Union) Long-term value: 1210 mg/m³, 500 ppm		

· DNELs

128-37-0 Butylated hydroxytoluene

		0.5 mg/kg bw/day (man)
Inhalative	$DNEL\ inhalation$	3.5 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· Respiratory protection: Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio BOND

(Contd. of page 4)

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

Form: Liquid
Colour: Yellow
Odour: Acetone-like
Odour threshold: Not determined.

• pH-value at 20 °C: 1.8

· Change in condition

• Melting point/freezing point: -95 °C • Initial boiling point and boiling range: 55 °C • Flash point: -17 °C

Flammability (solid, gas): Highly flammable.
 Auto-ignition temperature: Undetermined.
 Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:

Lower:

Upper:

Vapour pressure:

Density at 20 °C:

Relative density

Vapour density

Not determined.

Not determined.

Not determined.

Not determined.

Not determined.

· Solubility in / Miscibility with

water: Insoluble.Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• Dynamic: Not determined. • Kinematic: Not determined.

(Contd. on page 6)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio_BOND

(Contd. of page 5)

· Solvent content:	
· Organic solvents:	33.0 %
· Water:	24.0 %
· VOC (EC)	400.6 g/l

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant	for	classi	fication:
---------------------------	-----	--------	-----------

67 61 1	acetone
0/-04-1	uceione

 Oral
 LD50
 5,800 mg/kg (rat (f+m))

 Dermal
 LD50
 20,000 mg/kg (rabbit)

128-37-0 Butylated hydroxytoluene

Oral |LD50| > 6,000 mg/kg (rat (f+m)) (OECD 401)

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging fertility or the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

Persistence and degradability No further relevant information available.

(Contd. on page 7)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio_BOND

(Contd. of page 6)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · NZS, IMDG, IATA

UN1090

- · UN proper shipping name
- · NZS · IMDG, IATA

1090 ACETONE

ACETONE

- · Transport hazard class(es)
- · NZS



- · Class 3 (F1) Flammable liquids.
- · Label

3

· IMDG, IATA



· Class 3 Flammable liquids.

(Contd. on page 8)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio_BOND

	(Contd. of
Label	3
Packing group	
NZS, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	E
Transport in bulk according to Annex II of Mar	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
NZS	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1090 ACETONE, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	d Inventory of Chemicals		
67-64-1	acetone		
7732-18-5	Water		
1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane		
70293-55-9	2-[(2-methyl-1-oxoallyl)oxy]ethyl 1,3-dihydro-1,3-dioxoisobenzofuran-5-carboxylate		
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica		
109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate		
10373-78-1	3-1 Camphorquinone		
75980-60-8 diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
128-37-0 Butylated hydroxytoluene			
1344-28-1 aluminium oxide			
10287-53-3 ethyl 4-dimethylaminobenzoate			
HSNO Appi	roval numbers		
67-64-1 ace	 Ptone	HSR00102	

(Contd. on page 9)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio BOND

(Contd. of page 8)

- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

07 GHS0

- · Signal word Danger
- · Hazard-determining components of labelling:

2,2'-ethylenedioxydiethyl dimethacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

· Hazard statements

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

(Contd. on page 10)

Printing date 20.07.2023 Version number 4 Revision: 20.07.2023

Trade name: G-Premio BOND

(Contd. of page 9)

H410 Very toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.



Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: G-Multi PRIMER
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · Details of the supplier of the safety data sheet Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

2,2'-ethylenedioxydiethyl dimethacrylate

· Hazard statements

Highly flammable liquid and vapour.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi PRIMER

(Contd. of page 1)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
	ethyl alcohol	90-<100%
EINECS: 200-578-6	Flam. Liq. 2, H225	
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	1-<2.5%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
	2,2'-ethylenedioxydiethyl dimethacrylate	1-<2.5%
EINECS: 203-652-6	Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Generally the product does not irritate the skin.

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water

(Contd. on page 3)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi PRIMER

(Contd. of page 2)

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/surface or ground water.

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Allow to evaporate.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi PRIMER

(Contd. of page 3)

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethyl alcohol

WES (New Zealand) Long-term value: 1880 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Suitable respiratory protective device recommended.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · General Information
- · Appearance:

· Form: Liquid
· Colour: Colourless

(Contd. on page 5)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi_PRIMER

(Contd. of page 4)

Odour: Alcohol-like
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

• Melting point/freezing point: -114.5 °C • Initial boiling point and boiling range: 78 °C • Flash point: 13 °C

· Flammability (solid, gas): Highly flammable.

· Auto-ignition temperature: 425 °C

• **Decomposition temperature:** Not determined.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: 3.5 Vol %
Upper: 15 Vol %
Vapour pressure at 20 °C: 59 hPa
Density at 20 °C: 0.8 g/cm³
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.

· Solubility in / Miscibility with

water at 20 °C: 1.000 g/l

Insoluble.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

• *Organic solvents*: 94.0 % • *VOC (EC)* 752.0 g/l

• *Other information* No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:		
64-17-5	ethyl alcoho	l	
Oral	LD50	7,060 mg/kg (rat (f+m))	

(Contd. on page 6)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi PRIMER

(Contd. of page 5)

Inhalative | LC50/4 h | 20,000 mg/l (rat (f+m))

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

1	4	T	rans	port	inj	format	ion

IIN	-Nu	mh	or

· NZS, IMDG, IATA UN1170

· UN proper shipping name

• NZS 1170 ETHANOL SOLUTION mixture • IMDG, IATA ETHANOL SOLUTION mixture

(Contd. on page 7)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi_PRIMER

	(Contd. of pa
Transport hazard class(es)	
NZS	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group NZS, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of Mary	
and the IBC Code	Not applicable.
Transport/Additional information:	
NZS	
Limited quantities (LQ)	IL .
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 500 ml 2
Tunnel restriction code	D/E
	2,2
IMDG Limited quantities (LQ)	IL
Excepted quantities (EQ)	1L Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Deculation":	UN 1170 ETHANOL SOLUTION MIXTURE, 3, II
UN "Model Regulation":	ON 11/0 EIHANOL SOLUHON WHATOKE, 3, H

- NZ

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi PRIMER

(Contd. of page 7)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

· New Zealan	· New Zealand Inventory of Chemicals		
64-17-5	ethyl alcohol		
2530-85-0	3-trimethoxysilylpropyl methacrylate		
109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate		
	2-Propenoic acid, 2-methyl-, polymer with (chloromethyl)oxirane and 4,4-(1-methylethylidene) bisphenol		

· HSNO Approval numbers

64-17-5 ethyl alcohol

HSR001144

- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:
- 2,2'-ethylenedioxydiethyl dimethacrylate
- · Hazard statements

Highly flammable liquid and vapour.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

· Department issuing SDS: Regulatory affairs

(Contd. on page 9)

Printing date 02.11.2023 Version number 4 Revision: 02.11.2023

Trade name: G-Multi PRIMER

(Contd. of page 8)

· Contact: msds@gc.dental

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.