



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: LiSi PressVest SR Liquid

Manufacturer: GC Corporation

SDS Expiry: 1 December 2027

Supplier Details: Henry Schein New Zealand

243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6

HSNO Group Standard: Dental Products Flammable Group Standard 2020 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – May 2023

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: GC LiSi PressVest SR Liquid
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- Details of the supplier of the safety data sheet

Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC LiSi PressVest SR Liquid

· vPvB: Not applicable.

(Contd. of page 1)

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

| · Dangerous components: | | |
|-------------------------|---|----------|
| CAS: 67-63-0 | isopropyl alcohol | 90-<100% |
| EINECS: 200-661-7 | Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

NZ

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC LiSi PressVest SR Liquid

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC LiSi PressVest SR Liquid

(Contd. of page 3)

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 isopropyl alcohol

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm Long-term value: 983 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

• pH-value at 20 °C: 6-8

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 82 °C

(Contd. on page 5)

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC_LiSi_PressVest_SR_Liquid

| | (Contd. of page |
|---|---|
| · Flash point: | 13 °C |
| Flammability (solid, gas): | Highly flammable. |
| Ignition temperature: | Undetermined. |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product does not present an explosion hazard. |
| Explosion limits: | |
| Lower: | 2 Vol % |
| Upper: | 12 Vol % |
| Vapour pressure: | Not determined. |
| Density: | Not determined. |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Insoluble. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | 95.2 % |
| VOC (EC) | 952.0 g/l |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

| · LD/LC50 values relevant for classification: | | |
|---|------|-------------------------|
| 67-63-0 isopropyl alcohol | | |
| Oral | LD50 | 4,570 mg/kg (rat (f+m)) |

(Contd. on page 6)

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC LiSi PressVest SR Liquid

(Contd. of page 5)

 Dermal
 LD50
 13,400 mg/kg (rab)

 Inhalative
 LC50/4 h
 30 mg/l (rat (f+m))

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

| 4 Transport information | | |
|---------------------------|--------------------------------|--|
| · UN-Number | | |
| · NZS, IMDG, IATA | UN1219 | |
| · UN proper shipping name | | |
| $\cdot NZS$ | 1219 ISOPROPYL ALCOHOL mixture | |
| · IMDG, IATA | ISOPROPYL ALCOHOL mixture | |
| | (Ct-l | |

(Contd. on page 7)

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC_LiSi_PressVest_SR_Liquid

| | (Contd. of pa |
|--|---|
| Transport hazard class(es) | |
| NZS | |
| | |
| | |
| 3 | |
| Class | 3 (F1) Flammable liquids. |
| Label | 3 |
| IMDG, IATA | |
| | |
| | |
| 3 | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| Packing group | |
| NZS, IMDG, IATA | II |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): EMS Number: | 33 E E S D |
| EMS Number: Stowage Category | F-E,S-D B |
| | |
| Transport in bulk according to Annex II of Marq and the IBC Code | poi Not applicable. |
| | тог аррисаете. |
| Transport/Additional information: | |
| NZS Limited quantities (LQ) | IL |
| Excepted quantities (EQ) | Code: E2 |
| =neepren quantities (= 2) | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| Transport category | 2 |
| Tunnel restriction code | D/E |
| IMDG | |
| Limited quantities (LQ) | IL |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| UN "Model Deculation": | UN 1219 ISOPROPYL ALCOHOL MIXTURE, 3, II |
| UN "Model Regulation": | ON 1219 ISOF ROF IL ALCOHOL MIATURE, 3, II |

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC LiSi PressVest SR Liquid

(Contd. of page 7)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

67-63-0 isopropyl alcohol

HSR001180

- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Printing date 01.12.2022 Version number 3 Revision: 01.12.2022

Trade name: GC LiSi PressVest SR Liquid

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- · * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

N7