Company Logo

SAFETY DATA SHEET

According to HSNO Hazardous Substances (Safety Data Sheets) Notice 2017

Section 1. Identification of the material and the supplier

Product: W & H Service Oil F1 MD 200 1x

Article No: 028114
Product Use: Lubricating oil

Restriction of Use: Restricted to professional users.

New Zealand Supplier: Ivoclar Vivadent Ltd

Address: 12 Omega St

Rosedale

Auckland 0632, New Zealand PO Box 303011, North Harbour

Auckland, 0751

Telephone: +64 9 914 9999

E-Mail: orders.nz@ivoclarvivadent.com

Emergency No: 0800 764 766 (National Poison Centre)

Manufacturer: Klüber Lubrication München

Address: Geisenhausenerstr. 7

81379 München Deutschland

Telephone: +49 (0) 89 7876 0

Date of SDS Preparation: 14 November 2019

Section 2. Hazards Identification

The manufacturer has stated that this substance is NOT hazardous according to the EPA Hazardous Substances (Classification) Notice 2017 and GHS classification system.

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Synthetic hydrocarbon oil	To 100	Proprietary
ester oil		

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Rinse immediately with plenty of water, also under the eyelids, for at least

10 minutes. If eye irritation persists, consult a specialist.

If on Skin Remove contaminated clothing. If irritation develops, get medical

attention. In case of contact, immediately flush skin with plenty of water

If Swallowed Do not induce vomiting. Wash out mouth thoroughly with water. Never

give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek medical attention

if needed.

Product Name: W & H Service Oil F1 MD 200 1x Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 14 November 2019 Tel: 64 9 475 5240 www.techcomp.co.nz

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes

difficult.

Most important symptoms and effects, both acute and delayed

Symptoms: None known.

Section 5.	Fire Fighting Measures
------------	------------------------

Hazard Type	Non Flammable
Hazards from combustion products	Fire may cause evolution of: Carbon oxides
Suitable Extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Do not use a high volume water jet.
Precautions for firefighters and special protective clothing	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
HAZCHEM CODE	None Allocated

Section 6. Accidental Release Measures

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel.

Do not allow to enter drains and water courses.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Section 7. Handling and Storage

Precautions for Handling:

- For personal protection see section 8.
- Smoking, eating and drinking should be prohibited in the application area.
- Wash hands and face before breaks and immediately after handling the product.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store in original container.
- Keep container closed when not in use.
- Keep in a dry, cool and well-ventilated place.
- Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Keep in properly labelled containers.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term

Product Name: W & H Service Oil F1 MD 200 1x
Date of SDS: 14 November 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

Engineering Controls

None known.

Personal Protection Equipment





Eyes	Safety glasses with side-shields conforming to EN166
Skin	For prolonged or repeated contact use Nitrile rubber gloves.
Respiratory	Not required; except in case of aerosol formation. Filter type A-P

Section 9 Physical and Chemical Properties

Appearance	Liquid
	•
Colour	Yellow
Odour	Characteristic
Odour Threshold	Not available
pH	Not available
Boiling Point	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	>200°C (open cup)
Flammability	Not available
Upper and Lower	Not available
Explosive Limits	
Vapour Pressure	< 0.001 hPa (20 °C)
Vapour Density	0.85 g/cm3 (20 °C)
Specific Gravity	Not available
Water Solubility	Insoluble
Partition Coefficient:	Not available
Auto-ignition	Not available
Temperature	
Decomposition	Not available
Temperature	
Kinematic Viscosity	25 mm2/s (40 °C)
Particle Characteristics	Not available

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous	Not available
reactions	
Conditions to Avoid	None known.
Incompatible Materials	None known.
Hazardous Decomposition	Fire may cause evolution of: Carbon oxides
Products	

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.

Product Name: W & H Service Oil F1 MD 200 1x Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 14 November 2019 Tel: 64 9 475 5240 www.techcomp.co.nz

Inhalation	Not applicable.
Eye	Not applicable.
Skin	Not applicable.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Product:	
Persistence and degradability	No data available
Bioaccumulation	Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).
Mobility in Soil	No data available
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method:

Triple rinse container and dispose of according to Local Regulations.

Precautions or methods to avoid: Avoid release to the environment.

Section 14	Transport Information	
Section 14	Transport Information	

This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2012

Section 15 Regulatory Information

The manufacturer has stated that this substance is NOT hazardous according to the EPA Hazardous Substances (Classification) Notice 2017 and GHS classification system.

Section 16	Other Information
Glossary	
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms
	inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible

Product Name: W & H Service Oil F1 MD 200 1x
Date of SDS: 14 November 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

authority.

UEL Upper Explosive Level Workplace Exposure Limit WES

References:

- EPA Hazardous Substances (Safety Data Sheets) Notice 2017 1.
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-todate information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

14 November 2019 14 November 2024 Issue Date: Review Date:

Prepared by: Technical Compliance Consultants (NZ) Ltd Product Name: W & H Service Oil F1 MD 200 1x

Date of SDS: 14 November 2019 Tel: 64 9 475 5240 www.techcomp.co.nz