



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: QUATTROcare plus Spray

Manufacturer: KaVo Dental GmbH

SDS Expiry: 11 June 2026

Supplier Details: Henry Schein New Zealand

23 William Pickering Drive, Albany

PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 2

HSNO Group Standard: Aerosols Flammable Group Standard 2020 HSR002515

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared - June 2021

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 1 of 10

Revision date: 11.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

KaVo QUATTROcare plus Spray

Product code:

1.011.4624 1.011.5720

Further trade names

QUATTROcare plus Spray 2140, QUATTROcare plus Spray 2140P

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: KaVo Dental GmbH Street: Bismarckring 39 Place: D-88400 Biberach

Telephone: +49 (0) 7351 56 0 Telefax: + 49 (0) 7351 56 1488

e-mail: sdb@kavo.com

e-mail (Contact person): support@gefahrstoff.com

Internet: www.kavo.com

Responsible Department: Questions concerning SDB: PES-Ingenieurgesellschaft mbH

Supplier

Company name: Kavo Kerr Australia

Level 4

Street: 7 Eden Park Drive

Place: Macquarie Park, NSW 2113

1.4. Emergency telephone Infotrac/GBK GmbH +61-280735031

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

UN-GHS (Rev.7)

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

2.2. Label elements

UN-GHS (Rev.7)

Signal word: Danger

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 2 of 10

Revision date: 11.06.2021

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of waste according to applicable legislation.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | Quantity |
|-----------|-------------------------------|-------------|
| 106-97-8 | butane | 25 - < 50 % |
| 75-28-5 | isobutane | 25 - < 50 % |
| 8042-47-5 | White mineral oil (petroleum) | 10 - < 20 % |
| 74-98-6 | propane | 5 - < 10 % |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 3 of 10

Revision date: 11.06.2021

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness. May cause drowsiness or dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder. Water mist.

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

In case of fire may be liberated: Gases/vapours, toxic (Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protective suit. In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Remove persons to safety. Evacuate area. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Ventilate affected area. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 4 of 10

Revision date: 11.06.2021

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use. Do not pierce or burn, even after use. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Wear personal protection equipment.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect against: frost. Protect against direct sunlight. Protect from sunlight.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|----------|-----------|-----|-------|-----------|---------------|--------|
| 106-97-8 | Butane | 600 | 1450 | | TWA (8 h) | WEL |
| | | 750 | 1810 | | STEL (15 min) | WEL |

Additional advice on limit values

Occupational exposure limit values:

butane (106-97-8):

TWA: 800 ppm 1900 mg/m³ STEL: - ppm - mg/m³

propane (74-98-6):

Asphyxiant in high concentrations. (see Chapter 10 - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment, published by Worksafe Australia)

Source: Workplace exposure standards for airborne contaminants, Publication date: 16 December 2019

8.2. Exposure controls







Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 5 of 10

Revision date: 11.06.2021

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Take off contaminated clothing. Draw up and observe skin protection programme. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

Hand protection

Wear suitable gloves.

Protect skin by using skin protective cream.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Protect skin by using skin protective cream.

Suitable material: NBR (Nitrile rubber)

Breakthrough time (maximum wearing time) 480 min. Thickness of the glove material: 0,45 mm

Skin protection

Wear suitable gloves. Flame-retardant protective clothing. Wear anti-static footwear and clothing Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Respiratory protection necessary at: exceeding exposure limit values.

Suitable respiratory protection apparatus:

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment. Explosion risk. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light yellow
Odour: characteristic

Test method

pH-Value: not determined DIN 19268

Changes in the physical state

Melting point: not determined

Boiling point or initial boiling point and -40 °C

boiling range:

Flash point: -80 °C

Flammability

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 6 of 10

Revision date: 11.06.2021

Solid: not applicable
Gas: not applicable

Explosive properties

Heating may cause an explosion. Vapours can form explosive mixtures with air.

Lower explosion limits: 0,9 vol. % Upper explosion limits: 15 vol. %

Self-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,853 g/cm³ DIN 51757

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Viscosity / dynamic:

Viscosity / kinematic:

Relative vapour density:

Evaporation rate:

not determined

not determined

not determined

9.2. Other information

Odour threshold: not determined.

Relative density, Colour, Odour, Viscosity, pH: Data apply to the technically active substance.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Protect against direct sunlight. Protect against: Frost. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gases/vapours, toxic (Carbon dioxide (CO2), Carbon monoxide, aldehydes,

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 7 of 10

Revision date: 11.06.2021

carbon black)

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | | | | | |
|-----------|-------------------------------|----------------------|--------|--------------|--------|--|
| | Exposure route | posure route Dose | | Source | Method | |
| 8042-47-5 | White mineral oil (petroleum) | | | | | |
| | oral | LD50 > 5000 mg/kg | Rat | Manufacturer | | |
| | dermal | LD50 > 2000 mg/kg | Rabbit | Manufacturer | | |
| | inhalation (4 h) aerosol | LC50 > 5000 mg/l | Rat | Manufacturer | | |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience

Other observations

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 8 of 10

Revision date: 11.06.2021

| CAS No | Chemical name | | | | | | |
|-----------|-------------------------------|---------------|-------|-----------|-----------------------------------|--------------|--------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 8042-47-5 | White mineral oil (petroleum) | | | | | | |
| | Acute fish toxicity | LC50 mg/l | > 100 | 96 h | Brachydanio rerio (zebra-fish) | Manufacturer | |
| | Acute algae toxicity | ErC50 mg/l | > 100 | | Desmodesmus subspicatus | Manufacturer | |
| | Acute crustacea toxicity | EC50 mg/l | > 100 | | Daphnia magna (Big water flea) | Manufacturer | |

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|-----------|-------------------------------|---------|
| 106-97-8 | butane | 1,09 |
| 75-28-5 | isobutane | 1,09 |
| 8042-47-5 | White mineral oil (petroleum) | > 3,5 |
| 74-98-6 | propane | 1,09 |

12.4. Mobility in soil

The product has not been tested.

12.5. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Special Provisions: 63 190 277 327 344 381

Limited quantity: 1 L
Excepted quantity: E0

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 9 of 10

Revision date: 11.06.2021

Other applicable information (land transport)

HAZCHEM: - HIN (1)

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:

IATA-max. quantity - Passenger:

IATA-packing instructions - Cargo:

IATA-max. quantity - Cargo:

150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet



according to the Preparation of Safety data Sheets for Hazardous Chemicals Code of Practice

Page 10 of 10

Revision date: 11.06.2021

National regulatory information

AICS (AICIS/NICNAS):

CAS No. 75-28-5: Yes. (IMAP tier I assessment: available) CAS No. 8042-47-5: Yes. (IMAP tier I assessment: available) CAS No. 74-98-6: Yes. (IMAP tier I assessment: available)

CAS No. 106-97-8: Yes. (IMAP tier I assessment: available)

SUSMP:

CAS No. 75-28-5: No. CAS No. 8042-47-5: No. CAS No. 74-98-6: No. CAS No. 106-97-8: No.

Observe in addition any national regulations!

SECTION 16: Other information

Abbreviations and acronyms

ADG: Australian Dangerous Goods

AICS: Australian Inventory of Chemical Substances

AICIS: Australian Industrial Chemicals Instroduction Scheme

NICNAS: National Industrial Chemicals Notification and Assessment Scheme

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NICNAS: National Industrial Chemicals Notification and Assessment Scheme

SETEL: Short Term Exposure Limits TWA: Time-Weighted Average

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)