

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: ZipBond Universal - dental adhesive

Manufacturer: SDI

SDS Expiry: 22 August 2024

Supplier Details: Henry Schein New Zealand  
23 William Pickering Drive, Albany  
PO Box 101 140, North Shore, Auckland 0745  
Ph. 0800 808 855  
[www.henryschein.co.nz](http://www.henryschein.co.nz)

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –  
0800POISON/0800764766 (24 Hours)  
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3, 6

HSNO Group Standard: Dental Products Flammable Group Standard 2017 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared on 16 November 2020

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



## ZipBond Universal - dental adhesive

SDI (North America) Inc.

Version No: 3.1.1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 25/01/2019

Print Date: 22/08/2019

L.GHS.USA.EN

### SECTION 1 IDENTIFICATION

#### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | ZipBond Universal - dental adhesive                                      |
| Synonyms                      | Not Available  |
| Proper shipping name          | Ethanol or Ethyl alcohol or Ethanol solutions or Ethyl alcohol solutions |
| Other means of identification | Not Available  |

#### Recommended use of the chemical and restrictions on use

|                          |  |
|--------------------------|--|
| Relevant identified uses | Professional dental use: Dental bonding agent. |
|--------------------------|--|

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

| Registered company name | SDI (North America) Inc.                            | SDI Limited                                      | SDI Brazil Industria E Comercio Ltda                                   |
|-------------------------|---|--|--|
| Address                 | 1279 Hamilton Parkway Itasca IL 60143 United States | 3-15 Brunson Street Bayswater VIC 3153 Australia | Rua Dr. Virgilio de Carvalho Pinto, 612 São Paulo CEP 05415-020 Brazil |
| Telephone               | +1 630 361 9200                                     | +61 3 8727 7111                                  | +55 11 3092 7100   |
| Fax                     | Not Available                                       | +61 3 8727 7222                                  | +55 11 3092 7101   |
| Website                 | Not Available                                       | www.sdi.com.au                                   | www.sdi.com.au   |
| Email                   | Not Available                                       | info@sdi.com.au                                  | brasil@sdi.com.au  |

| Registered company name | SDI Germany GmbH                        |
|-------------------------|---|
| Address                 | Hansestrasse 85 Cologne D-51149 Germany |
| Telephone               | +49 0 2203 9255 0                       |
| Fax                     | +49 0 2203 9255 200                     |
| Website                 | www.sdi.com.au                          |
| Email                   | germany@sdi.com.au                      |

#### Emergency phone number

| Association / Organisation        | SDI (North America) Inc. | SDI Limited     |
|-----------------------------------|--------------------------|-----------------|
| Emergency telephone numbers       | +61 3 8727 7111          | +61 3 8727 7111 |
| Other emergency telephone numbers | Not Available            | 131126          |

### SECTION 2 HAZARD(S) IDENTIFICATION

#### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

|                |   |
|----------------|---|
| Classification | Flammable Liquid Category 2, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Skin Sensitizer Category 1 |
|----------------|---|

#### Label elements

|                     |  |
|---------------------|--|
| Hazard pictogram(s) |  |
|---------------------|--|

|             |        |
|-------------|--------|
| SIGNAL WORD | DANGER |
|-------------|--------|

Continued...

## ZipBond Universal - dental adhesive

## Hazard statement(s)

|      |                                      |
|------|--------------------------------------|
| H225 | Highly flammable liquid and vapour.  |
| H315 | Causes skin irritation.              |
| H319 | Causes serious eye irritation.       |
| H317 | May cause an allergic skin reaction. |

## Hazard(s) not otherwise classified

Not Applicable

## Precautionary statement(s) Prevention

|      |   |
|------|---|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.                |
| P233 | Keep container tightly closed.  |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.        |
| P240 | Ground/bond container and receiving equipment.                                    |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| P242 | Use only non-sparking tools.  |
| P243 | Take precautionary measures against static discharge.                             |
| P261 | Avoid breathing mist/vapours/spray.   |
| P272 | Contaminated work clothing should not be allowed out of the workplace.            |

## Precautionary statement(s) Response

|                |  |
|----------------|--|
| P321           | Specific treatment (see advice on this label).   |
| P362           | Take off contaminated clothing and wash before reuse.  |
| P370+P378      | In case of fire: Use alcohol resistant foam or normal protein foam for extinction.   |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.                       |

## Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
|-----------|--|

## Precautionary statement(s) Disposal

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## Substances

See section below for composition of Mixtures

## Mixtures

| CAS No        | %[weight] | Name            |
|---------------|-----------|-----------------|
| 64-17-5       | 30-35     | <u>ethanol</u>  |
| Not Available | 40-50     | acrylic monomer |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## SECTION 4 FIRST-AID MEASURES

## Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>                                      |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul> |

Continued...

## ZipBond Universal - dental adhesive

**Ingestion**

If irritation continues, seek medical attention.  
If conscious, give water to drink.

**Most important symptoms and effects, both acute and delayed**

See Section 11

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 FIRE-FIGHTING MEASURES****Extinguishing media**

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

**Special hazards arising from the substrate or mixture****Fire Incompatibility**

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

**Special protective equipment and precautions for fire-fighters**

|                              |   |
|------------------------------|---|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ Fight fire from a safe distance, with adequate cover.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>Do not approach containers suspected to be hot.</b></li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include:<br/>carbon dioxide (CO<sub>2</sub>)<br/>other pyrolysis products typical of burning organic material.</p>   |

**SECTION 6 ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> <li>▶ Collect residues in a flammable waste container.</li> </ul>  |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse /absorb vapour.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Use only spark-free shovels and explosion proof equipment.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## ZipBond Universal - dental adhesive

## SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> <li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>▶ Vapour may ignite on pumping or pouring due to static electricity.</li> <li>▶ <b>DO NOT use plastic buckets.</b></li> <li>▶ Earth and secure metal containers when dispensing or pouring product.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>  |

## Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li> <li>▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li> <li>▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</li> <li>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li> <li>▶ <b>DO NOT repack.</b> Use containers supplied by manufacturer only.</li> <li>▶ Check that containers are clearly labelled and free from leaks</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid strong bases.</li> </ul>   |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

| Source  | Ingredient | Material name   | TWA                   | STEL          | Peak          | Notes               |
|---|------------|---|-----------------------|---------------|---------------|---------------------|
| US NIOSH Recommended Exposure Limits (RELs)           | ethanol    | Alcohol, Cologne spirit, Ethanol, EtOH, Grain alcohol | 1000 ppm / 1900 mg/m3 | Not Available | Not Available | Not Available       |
| US ACGIH Threshold Limit Values (TLV)                 | ethanol    | Ethanol   | Not Available         | 1000 ppm      | Not Available | TLV® Basis: URT irr |
| US OSHA Permissible Exposure Levels (PELs) - Table Z1 | ethanol    | Ethyl alcohol (Ethanol)                               | 1000 ppm / 1900 mg/m3 | Not Available | Not Available | Not Available       |

## EMERGENCY LIMITS


| Ingredient | Material name            | TEEL-1        | TEEL-2        | TEEL-3    |
|------------|--------------------------|---------------|---------------|-----------|
| ethanol    | Ethyl alcohol; (Ethanol) | Not Available | Not Available | 15000 ppm |
| Ingredient | Original IDLH            | Revised IDLH  |               |           |
| ethanol    | 3,300 ppm                | Not Available |               |           |

## MATERIAL DATA

## Exposure controls

|   |   |
|---|---|
| <b>Appropriate engineering controls</b> | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> |
|---|---|

## ZipBond Universal - dental adhesive

|   |   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
|---|---|----------------------|------------|--|---------------------------------|---|-------------------------------|--|-------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
|   | <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1"> <tr> <td>Type of Contaminant:</td> <td>Air Speed:</td> </tr> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s<br/>(50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s<br/>(100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s<br/>(200-500 f/min.)</td> </tr> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <tr> <td>Lower end of the range</td> <td>Upper end of the range</td> </tr> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s<br>(50-100 f/min.) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s<br>(200-500 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
| Type of Contaminant:  | Air Speed:  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s<br>(50-100 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s<br>(200-500 f/min.)   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Lower end of the range  | Upper end of the range  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Personal protection</b>  |   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Eye and face protection</b>  | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Skin protection</b>  | See Hand protection below   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Hands/feet protection</b>  | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>▶ Rubber Gloves</li> <li>▶ Nitrile rubber gloves</li> </ul>  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Body protection</b>  | See Other protection below  |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| <b>Other protection</b>   | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> </ul>   |                      |            |  |                                 |   |                               |  |                               |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |

**Respiratory protection**

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 5 x ES                       | Air-line*            | A-2                  | A-PAPR-2 ^             |
| up to 10 x ES                      | -                    | A-3                  | -                      |
| 10+ x ES                           | -                    | Air-line**           | -                      |

\* - Continuous Flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

|                       |  |                                     |       |
|-----------------------|--|-------------------------------------|-------|
| <b>Appearance</b>     | Yellow liquid with slightly characteristic odour, does not mix in water. |                                     |       |
| <b>Physical state</b> | Liquid   | <b>Relative density (Water = 1)</b> | 1-1.2 |

Continued...

## ZipBond Universal - dental adhesive

|   |                |  |                |
|---|----------------|--|----------------|
| <b>Odour</b>  | Not Available  | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available  | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | ~3.0           | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Applicable | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | >78            | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Available  | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Available  | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available  | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available  | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water</b>                          | Immiscible     | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available  | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence. In the absence of such evidence, care should be taken nevertheless to ensure exposure is kept to a minimum and that suitable control measures be used, in an occupational setting to control vapours, fumes and aerosols. Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination  |
| <b>Ingestion</b>    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.   |
| <b>Skin Contact</b> | Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br><br>Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. |
| <b>Eye</b>          | Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.<br>Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.  |
| <b>Chronic</b>      | Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.<br>Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.  |

|  |   |  |
|--|---|--|
| <b>ZipBond Universal - dental adhesive</b> | <b>TOXICITY</b>                                     | <b>IRRITATION</b>  |
|  | Not Available                                       | Not Available  |
| <b>ethanol</b>                             | <b>TOXICITY</b>                                     | <b>IRRITATION</b>  |
|  | Inhalation (rat) LC50: 124.7 mg/l/4H <sup>[2]</sup> | Eye (rabbit): 500 mg SEVERE                              |
|  | Oral (rat) LD50: =1501 mg/kg <sup>[2]</sup>         | Eye (rabbit):100mg/24hr-moderate                         |
|  |   | Eye: adverse effect observed (irritating) <sup>[1]</sup> |
|  |   | Skin (rabbit):20 mg/24hr-moderate                        |

## ZipBond Universal - dental adhesive

Skin (rabbit):400 mg (open)-mild

Skin: no adverse effect observed (not irritating)<sup>[1]</sup>

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

## ETHANOL

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✗ | Carcinogenicity          | ✗ |
| Skin Irritation/Corrosion         | ✓ | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation     | ✓ | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation | ✓ | STOT - Repeated Exposure | ✗ |
| Mutagenicity                      | ✗ | Aspiration Hazard        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| ZipBond Universal - dental adhesive | ENDPOINT      | TEST DURATION (HR) | SPECIES       | VALUE         | SOURCE        |
|-------------------------------------|---------------|--------------------|---------------|---------------|---------------|
|                                     | Not Available | Not Available      | Not Available | Not Available | Not Available |

| ethanol | ENDPOINT | TEST DURATION (HR) | SPECIES                       | VALUE        | SOURCE |
|---------|----------|--------------------|-------------------------------|--------------|--------|
|         | LC50     | 96                 | Fish                          | 11-mg/L      | 2      |
|         | EC50     | 48                 | Crustacea                     | 2mg/L        | 4      |
|         | EC50     | 96                 | Algae or other aquatic plants | 17.921mg/L   | 4      |
|         | NOEC     | 2016               | Fish                          | 0.000375mg/L | 4      |

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

| Ingredient | Persistence: Water/Soil     | Persistence: Air            |
|------------|-----------------------------|-----------------------------|
| ethanol    | LOW (Half-life = 2.17 days) | LOW (Half-life = 5.08 days) |

## Bioaccumulative potential

| Ingredient | Bioaccumulation      |
|------------|----------------------|
| ethanol    | LOW (LogKOW = -0.31) |

## Mobility in soil

| Ingredient | Mobility       |
|------------|----------------|
| ethanol    | HIGH (KOC = 1) |

## SECTION 13 DISPOSAL CONSIDERATIONS

## Waste treatment methods

|                              |  |
|------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> </ul> Consult State Land Waste Management Authority for disposal. |
|------------------------------|--|

## SECTION 14 TRANSPORT INFORMATION

## Labels Required



## ZipBond Universal - dental adhesive

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant | NO  |

## Land transport (DOT)

|                              |  |
|------------------------------|--|
| UN number                    | 1170   |
| UN proper shipping name      | Ethanol or Ethyl alcohol or Ethanol solutions or Ethyl alcohol solutions |
| Transport hazard class(es)   | Class : 3<br>Subrisk : Not Applicable                                    |
| Packing group                | II   |
| Environmental hazard         | Not Applicable   |
| Special precautions for user | Hazard Label : 3<br>Special provisions : 24, IB2, T4, TP1                |

## Air transport (ICAO-IATA / DGR)

|                              |   |
|------------------------------|---|
| UN number                    | 1170  |
| UN proper shipping name      | Ethanol or Ethanol. Solution  |
| Transport hazard class(es)   | ICAO/IATA Class : 3<br>ICAO / IATA Subrisk : Not Applicable<br>ERG Code : 3L  |
| Packing group                | II  |
| Environmental hazard         | Not Applicable  |
| Special precautions for user | Special provisions : A3 A58 A180<br>Cargo Only Packing Instructions : 364<br>Cargo Only Maximum Qty / Pack : 60 L<br>Passenger and Cargo Packing Instructions : 353<br>Passenger and Cargo Maximum Qty / Pack : 5 L<br>Passenger and Cargo Limited Quantity Packing Instructions : Y341<br>Passenger and Cargo Limited Maximum Qty / Pack : 1 L |

## Sea transport (IMDG-Code / GGVSee)

|                              |  |
|------------------------------|--|
| UN number                    | 1170   |
| UN proper shipping name      | ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)           |
| Transport hazard class(es)   | IMDG Class : 3<br>IMDG Subrisk : Not Applicable                                |
| Packing group                | II   |
| Environmental hazard         | Not Applicable   |
| Special precautions for user | EMS Number : F-E , S-D<br>Special provisions : 144<br>Limited Quantities : 1 L |

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

If packed as Chemical kits the following classification may be considered if all ICAO/IATA transport requirements are met: Chemical Kit UN3316 - Class 9.

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

ETHANOL(64-17-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

## ZipBond Universal - dental adhesive

|   |   |
|---|---|
| GESAMP/EHS Composite List - GESAMP Hazard Profiles  | US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants                           |
| IMO IBC Code Chapter 17: Summary of minimum requirements  | US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants         |
| IMO IBC Code Chapter 18: List of products to which the Code does not apply  | US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants       |
| IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances   | US - Washington Permissible exposure limits of air contaminants                                     |
| IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO                           | US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants                    |
| IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards | US ACGIH Threshold Limit Values (Spanish)   |
| International Air Transport Association (IATA) Dangerous Goods Regulations  | US ACGIH Threshold Limit Values (TLV)   |
| International Maritime Dangerous Goods Requirements (IMDG Code)   | US ACGIH Threshold Limit Values (TLV) - Carcinogens   |
| United Nations Recommendations on the Transport of Dangerous Goods Model Regulations  | US AIHA Workplace Environmental Exposure Levels (WEELs)   |
| US - Alaska Limits for Air Contaminants   | US Department of Transportation (DOT), Hazardous Material Table                                     |
| US - California Permissible Exposure Limits for Chemical Contaminants   | US DOE Temporary Emergency Exposure Limits (TEELs)  |
| US - Hawaii Air Contaminant Limits  | US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk Liquid Cargoes |
| US - Idaho - Limits for Air Contaminants  | US NIOSH Recommended Exposure Limits (RELs)   |
| US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits   | US NIOSH Recommended Exposure Limits (RELs) (Spanish)   |
| US - Massachusetts - Right To Know Listed Chemicals   | US OSHA Permissible Exposure Levels (PELs) - Table Z1   |
| US - Michigan Exposure Limits for Air Contaminants  | US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)                                 |
| US - Minnesota Permissible Exposure Limits (PELs)   | US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide                |
| US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens   | US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID) Number   |
| US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Mutagens  | US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants                    |
| US - Oregon Permissible Exposure Limits (Z-1)   | US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory                               |
| US - Pennsylvania - Hazardous Substance List  | US TSCA Chemical Substance Inventory - Interim List of Active Substances                            |
| US - Rhode Island Hazardous Substance List  |   |

## Federal Regulations

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## SECTION 311/312 HAZARD CATEGORIES

|  |     |
|--|-----|
| Flammable (Gases, Aerosols, Liquids, or Solids)              | Yes |
| Gas under pressure   | No  |
| Explosive  | No  |
| Self-heating   | No  |
| Pyrophoric (Liquid or Solid)                                 | No  |
| Pyrophoric Gas   | No  |
| Corrosive to metal   | No  |
| Oxidizer (Liquid, Solid or Gas)                              | No  |
| Organic Peroxide   | No  |
| Self-reactive  | No  |
| In contact with water emits flammable gas                    | No  |
| Combustible Dust   | No  |
| Carcinogenicity  | No  |
| Acute toxicity (any route of exposure)                       | No  |
| Reproductive toxicity  | No  |
| Skin Corrosion or Irritation                                 | Yes |
| Respiratory or Skin Sensitization                            | Yes |
| Serious eye damage or eye irritation                         | Yes |
| Specific target organ toxicity (single or repeated exposure) | No  |
| Aspiration Hazard  | No  |
| Germ cell mutagenicity                                       | No  |
| Simple Asphyxiant  | No  |
| Hazards Not Otherwise Classified                             | No  |

## US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

## State Regulations

## US. CALIFORNIA PROPOSITION 65

None Reported

## National Inventory Status

| National Inventory | Status       |
|--------------------|--------------|
| Australia - AICS   | Yes          |
| Canada - DSL       | Yes          |
| Canada - NDSL      | No (ethanol) |

## ZipBond Universal - dental adhesive

|                               |  |
|-------------------------------|--|
| China - IECSC                 | Yes  |
| Europe - EINEC / ELINCS / NLP | Yes  |
| Japan - ENCS                  | Yes  |
| Korea - KECI                  | Yes  |
| New Zealand - NZIoC           | Yes  |
| Philippines - PICCS           | Yes  |
| USA - TSCA                    | Yes  |
| Taiwan - TCSI                 | Yes  |
| Mexico - INSQ                 | Yes  |
| Vietnam - NCI                 | Yes  |
| Russia - ARIPS                | Yes  |
| Thailand - TECl               | Yes  |
| <b>Legend:</b>                | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

**SECTION 16 OTHER INFORMATION**

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 25/01/2019 |
| <b>Initial Date</b>  | 16/05/2017 |

**SDS Version Summary**

| Version | Issue Date | Sections Updated   |
|---------|------------|--|
| 3.1.1.1 | 25/01/2019 | One-off system update. NOTE: This may or may not change the GHS classification |

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC – TWA: Permissible Concentration-Time Weighted Average  
 PC – STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

**Other information:**

Prepared by: SDI Limited  
 3-15 Brunson Street, Bayswater Victoria, 3153, Australia  
 Phone Number: +61 3 8727 7111  
 Department issuing SDS: Research and Development  
 Contact: Technical Director