



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: J-Temp™

Manufacturer: Ultradent

SDS Expiry: 3 August 2028

Supplier Details: Henry Schein New Zealand

243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 6

HSNO Group Standard: Dental Products Subsidiary Hazard Group Standard 2020

HSR002558

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – September 2023

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 03.08.2023 Revision: 03.08.2023

1 Identification

- · Product identifier
- · Trade name: J-TempTM
- · Article number: SDS 445-001.02R02, 1007685
- · Relevant identified uses of the substance or mixture and uses advised against Light-Cured Temporary Resin
- · Application of the substance / the mixture Light-Cured Temporary Resin
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products, Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

onlineordersupport@ultradent.com

Ultradent Australia Pty Ltd.

Level 22/2 Market Street

Sydney NSW 2000

Australia

Email: info.anz@ultradent.com Toll Free: 1-800-290929

- · Further information obtainable from: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazard(s) Identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms GHS07
- · Signal word Warning
- · Hazard-determining components of labelling:

Triethylene Glycol Dimethacrylate

Hydroxypropyl Methacrylate

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

(Contd. of page 1) · Precautionary statements If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves / eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. P333+P313 P337+P313 If eye irritation persists: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/national/international P501

3 Composition and Information on Ingredients

regulations.

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous co	omponents:	
109-16-0	Triethylene Glycol Dimethacrylate	>1-<10%
	♦ Skin Sens. 1, H317	
20882-04-6	Mono-2-(Methacryloyloxy) Ethyl Succinate	>1-<10%
	💠 Skin Irrit. 2, H315; Serious eye damage/irritation — Category 2A, H319	
27813-02-1	Hydroxypropyl Methacrylate	>1-<10%
	♦ Serious eye damage/irritation – Category 2A, H319; Skin Sens. 1, H317	
	Trade Secret	>0.1-<5%
	♦ Skin Corr. 1A, H314; Eye Dam. 1, H318	
79-41-4	Methacrylic Acid	<1%
	Acute Tox. 3, H331; Skin Corr. 1A, H314; Eye Dam. 1, H318; 1 Acute Tox. 4, H302; Acute Tox. 4, H312; Flam. Liq. 4, H227	
162881-26-7	Organophosphine Oxide	<1%
	♦ Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

· Suitable extinguishing agents:

Water spray, fog, or mist, foam, dry chemical, carbon dioxide

Use fire extinguishing methods suitable to surrounding conditions.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: Wear fully protective suit.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

See product labelling.

Keep container tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

79-41-4 Methacrylic Acid

WES Long-term value: 70 mg/m³, 20 ppm

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

(Contd. of page 3)

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

· Form: Medium Viscosity

· Colour: Violet

· Odour: Characteristic
· Odour threshold: Not determined.

· pH-value: Not applicable (non-aqueous)

· Change in condition

Melting point/freezing point:
 Initial boiling point and boiling range:
 Flash point:
 Flammability (solid, gas):
 Decomposition temperature:
 Undetermined.
 Not applicable.
 Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

· Lower: Not determined.

(Contd. on page 5)

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

· Upper: Not determined.
· Vapour pressure: Not determined.

Vapour pressure: Not determined.
 Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

• water: Fully miscible. • Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity Stable
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values relev	ant for classification:
109-16-0 7	Triethylene (Glycol Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
	LC50 Fish	16.4 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (mouse)
79-41-4 M	ethacrylic A	lcid
Oral	LD50	1,250 mg/kg (mouse)
		1,060 mg/kg (rat)
		1,200 mg/kg (rabbit)
	LC50 Fish	86 mg/l (Fish)
Dermal	LD50	1,000 mg/kg (Guinea pig)
		500 mg/kg (rabbit)
Inhalative	LC50/4 h	7.1 mg/l (rat)
162881-26	-7 Organop	hosphine Oxide
Oral	LD50	>2,000 mg/kg (rat)
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.

(Contd. on page 6)

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

(Contd. of page 5)

- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aquatic toxicity:	
109-16-0 Triethylene Glycol Dim	ethacrylate
EC50	>100 mg/kg (Algae)
Biodegradability	28 days (Aerobic) (Biodegradability testing)
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)
79-41-4 Methacrylic Acid	
EC50	17,000 mg/kg (Algae)
	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
162881-26-7 Organophosphine O	Dxide
EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)
Toxicity to Aquatic Plants (static)	>0.26 mg/l (Plant) (Toxicity to algae)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of contents/container in accordance with international, federal, state, and local regulations.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

ΑU

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

(Contd. of page 6)

UN-Number		
ADG, IMDG, IATA	not regulated	
UN proper shipping name ADG, IMDG, IATA	not regulated	
Transport hazard class(es)		
ADG, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
ADG, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not Applicable	
Transport in bulk according to Annex I	I of Marpol	
and the IBC Code	Not applicable.	
UN "Model Regulation":	not regulated	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian In	nventory of Industrial Chemicals	
9033-79-8	Sodium Acrylate Copolymer	
109-16-0	Triethylene Glycol Dimethacrylate	
20882-04-6	Mono-2-(Methacryloyloxy) Ethyl Succinate	
27813-02-1	Hydroxypropyl Methacrylate	
	Trade Secret	
10287-53-3	Ethyl-4-Dimethylamino Benzoate	
79-41-4	Methacrylic Acid	
162881-26-7	Organophosphine Oxide	
10373-78-1	Camphorquinone	
75-56-9	Methyloxirane	
	Co-Cr-AL Spinel Blue Green	
1332-37-2	Red Iron Oxide	
14808-60-7	Silica Glass	
Standard for	the Uniform Scheduling of Medicines and Poisons	
75-56-9 Meth	hyloxirane	

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A chemical safety assessment has not been carried out.

Printing date 03.08.2023 Revision: 03.08.2023

Trade name: J-TempTM

(Contd. of page 7)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases from Section 3

H227 Combustible liquid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

· Department issuing SDS: Environmental, Health, and Safety

· Contact: Customer Service

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Serious eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

* * Data compared to the previous version altered.

AU