

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name:	UltraCal™ XS
Manufacturer:	Ultradent
SDS Expiry:	27 July 2028
Supplier Details:	Henry Schein New Zealand 243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745 Ph. 0800 808 855 www.henryschein.co.nz
Emergency Contacts:	Poisons/Hazardous Chemical Info Centre – 0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police
HSNO Class/Category:	8
HSNO Group Standard:	Dental Products Corrosive Group Standard 2020 HSR002555
Statements/Pictograms:	As per attached Safety Data Sheet (SDS)
Date Prepared:	This coversheet was prepared – September 2023

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



Page 1/7

Safety Data Sheet according to WHS Regulations

Printing date 27.07.2023

*

Revision: 27.07.2023

	ion	
Product iden	tifier	
	UltraCal TM XS	
Relevant ide		Line
Manufacture Ultradent Pr. 505 W. Ultra South Jordan USA onlineorders Ultradent Au Level 22/2 M Sydney NSW Australia Email: info.a Toll Free: 1- Not applicab Further info Emergency t CHEMTREC	oducts, Inc. dent Drive (10200 S) , UT 84095-3942 upport@ultradent.com stralia Pty Ltd. arket Street 2000 nz@ultradent.com 800-290929	
Hazard(s)		
	Identification	
Classification		
Classification	Identification n of the substance or mixture rrosion	
Classification co co Skin Corr. 12 Eye Dam. 1 Label elemen GHS label el	Identification n of the substance or mixture rrosion 1 H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. tts ements Void grams GHS05	
Classification Classification Corr. 12 Eye Dam. 1 Label elemen GHS label el Hazard picto Signal word Hazard-deten	Identification n of the substance or mixture rrosion 1 H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. tts ements Void grams GHS05 Danger rmining components of labelling:	
Classification Classification Control 12 Eye Dam. 12 Label element GHS label element	Identification n of the substance or mixture rrosion 1 H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H318 Causes serious eye damage. tts ements Void grams GHS05 Danger rmining components of labelling: roxide ments severe skin burns and eye damage. y statements	
Classification Classification Construction Construction Construction Characteric Construction Co	Identification n of the substance or mixture rrosion 1 H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H5 ements Void grams GHS05 Danger rmining components of labelling: roxide ments severe skin burns and eye damage.	

Printing date 27.07.2023

Revision: 27.07.2023

(Contd. of mage 1)

Trade name: UltraCalTM XS

	(Contd. of page 1)
P260	Do not breathe dusts or mists.
P303+P361+P353	3 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
	with water/shower.
P305+P351+P338	B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

 \cdot **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
1305-62-0	Calcium Hydroxide	 Eye Dam. 1, H318	≥30- <i>≤</i> 60%
7727-43-7	Barium Sulfate		10-<30%
57-55-6	Propylene Glycol		<10%
Additional information: For the wording of the listed hazard phrases refer to section 16.			

4 First Aid Measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation:

This product is a thick paste, therefore inhalation is extremely unlikely.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

- *After eye contact:* Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

• Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

• Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

• Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

• *Protective equipment: Mouth respiratory protective device.*

6 Accidental Release Measures

• Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

• *Environmental precautions: Dilute with plenty of water.*

(Contd. on page 3)

AU

Printing date 27.07.2023

Revision: 27.07.2023

Trade name: UltraCalTM XS

(Contd. of page 2)

Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: Keep respiratory protective device available.

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- See product labelling.
- Keep container tightly sealed.

· Specific end use(s) Professional Dental Cavity Liner

8 Exposure controls and personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

1305-62-0 Calcium Hydroxide

WES Long-term value: 5 mg/m^3

7727-43-7 Barium Sulfate

WES Long-term value: 10 mg/m³ inhalable dust

57-55-6 Propylene Glycol

WES Long-term value: 474* 10** mg/m³, 150* ppm *vapour&particluates; **particulates only

· Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

AU

Printing date 27.07.2023

Revision: 27.07.2023

(Contd. of page 3)

AT

Trade name: UltraCalTM XS

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.



Tightly sealed goggles

· Body protection: Protective work clothing

General Information		
Appearance:		
Form:	Paste	
Colour:	White to off white	
Odour:	Odourless	
Odour threshold:	Not determined.	
pH-value at 20 °C:	12-13	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	Not determined.	
Density at 20 °C:	$1.4-1.5 \ g/cm^3$	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	

Printing date 27.07.2023

Revision: 27.07.2023

Trade name: UltraCalTM XS

		(Contd. of page 4)
· Viscosity: · Dynamic: · Kinematic:	Not determined. Not determined.	
• Other information	No further relevant information available.	

10 Stability and Reactivity

· Reactivity No further relevant information available.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant	for classification:
---------------------------	---------------------

· LD/LC50 values relevant for classification:			
1305-62-0 Calcium Hydroxide			
Oral	LD50	7,340 mg/kg (rat)	
7727-43	7727-43-7 Barium Sulfate		
Oral	LD50	>3,000 mg/kg (mouse)	
		307,000 mg/kg (rat)	
57-55-6 Propylene Glycol			
Oral	LD50	18,000 mg/kg (rabbit)	
	LC50 Fish	>5,000 mg/l (Fish)	
Dermal	LD50	20,800 mg/kg (rabbit)	

· Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information · Toxicity

• Aquatic toxicity:

7727-43-7 Barium Sulfate

EC50 32 mg/kg (daphnia)

57-55-6 Propylene Glycol

EC50 18,100 mg/kg (Algae)

(Contd. on page 6)

Printing date 27.07.2023

Revision: 27.07.2023

(Contd. of page 5)

Trade name: UltraCalTM XS

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.
- Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Do not allow product to reach sewage system.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of contents/container in accordance with international, federal, state, and local regulations.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

UN-Number ADG, IMDG, IATA	UN1719
UN proper shipping name ADG IMDG, IATA	1719 CAUSTIC ALKALI LIQUID, N.O.S. CAUSTIC ALKALI LIQUID, N.O.S.
Transport hazard class(es)	
S S S S S S S S S S S S S S S S S S S	
Class	8 Corrosive substances.
Label	8
Packing group	
ADG	II
Environmental hazards:	Not applicable.

S4

Safety Data Sheet according to WHS Regulations

Printing date 27.07.2023

Revision: 27.07.2023

Trade name: UltraCalTM XS

	(Contd. of page 6)
· EMS Number:	F-A,S-B
· Segregation groups	(SGG18) Alkalis
• Transport in bulk according to Annex II of Marpol	
and the IBC Code	Not applicable.
• Transport/Additional information:	
·ADG	
· Limited quantities (LQ)	1L
• Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. 8, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons

9004-65-3 Hydroxypropyl methyl cellulose

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- *Relevant phrases from Section 3* H318 Causes serious eye damage.
- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

* Data compared to the previous version altered.