



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: UltraSeal XT™ Hydro™

Manufacturer: Ultradent

SDS Expiry: 28 July 2028

Supplier Details: Henry Schein New Zealand

243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 6

HSNO Group Standard: Dental Products Subsidiary Hazard Group Standard 2020

HSR002558

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – September 2023

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 28.07.2023 Revision: 28.07.2023

### 1 Identification

- · Product identifier
- · Trade name: UltraSeal XTTM HydroTM
- · Article number: SDS 239-001.10R02, 71110, 71111, 71109
- · Relevant identified uses of the substance or mixture and uses advised against

Professional Dental Pit and Fissure Sealant

- · Application of the substance / the mixture Professional Dental Pit and Fissure Sealant
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products, Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

onlineordersupport@ultradent.com

Ultradent Australia Pty Ltd.

Level 22/2 Market Street

Sydney NSW 2000

Australia

Email: info.anz@ultradent.com Toll Free: 1-800-290929

- · Further information obtainable from: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA) :(800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

### 2 Hazard(s) Identification

· Classification of the substance or mixture



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements Void
- · Hazard pictograms GHS07
- · Signal word Warning
- · Hazard-determining components of labelling:

Triethylene Glycol Dimethacrylate

Diurethane Dimethacrylate

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

*Avoid breathing dust/fume/gas/mist/vapours/spray.* 

(Contd. on page 2)

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XTTM HydroTM

(Contd. of page 1)

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous co	omponents:	
109-16-0	Triethylene Glycol Dimethacrylate	>10-<30%
	<b>♦</b> Skin Sens. 1, H317	
72869-86-4	Diurethane Dimethacrylate	>5-<20%
	♦ Skin Sens. 1, H317	
	Trade Secret	>1-<10%
	🧇 Skin Corr. 1A, H314; Eye Dam. 1, H318	
13463-67-7	Titanium Dioxide	>1-<10%
	<b>♦</b> Carc. 2, H351	
79-41-4	Methacrylic Acid	≤l%
	Acute Tox. 3, H331; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Flam. Liq. 4, H227	
162881-26-7	Organophosphine Oxide	<1%
	♦ Skin Sens. 1, H317	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Seek medical treatment in case of complaints.

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire Fighting Measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XT<sup>TM</sup> Hydro<sup>TM</sup>

(Contd. of page 2)

#### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: See product labelling.
- · Specific end use(s) Professional Dental Pit and Fissure Sealant

#### 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

#### 13463-67-7 Titanium Dioxide

WES Long-term value: 10 mg/m<sup>3</sup>

inhalable dust

#### 79-41-4 Methacrylic Acid

WES Long-term value: 70 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XTTM HydroTM

(Contd. of page 3)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

#### 9 Physical and Chemical Properties

· General Information

· Appearance:

· Form: Liquid

· Colour: According to product specification

· Odour: Acrylic

· Odour threshold: Not determined.

· pH-value: Not applicable (non-aqueous)

· Change in condition

Melting point/freezing point:
 Initial boiling point and boiling range:
 Flash point:
 Flammability (solid, gas):
 Decomposition temperature:
 Undetermined.
 Not applicable.
 Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:
Vapour pressure:
Density at 20 °C:
Relative density
Vapour density
Vapour density
Not determined.

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

• Other information No further relevant information available.

#### 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.

(Contd. on page 5)

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XTTM HydroTM

(Contd. of page 4)

- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

		ant for classification:
		Glycol Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
		16.4 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (mouse)
72869-86-	4 Diurethan	ne Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
13463-67-	7 Titanium	Dioxide
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
79-41-4 M	ethacrylic A	lcid
Oral	LD50	1,250 mg/kg (mouse)
		1,060 mg/kg (rat)
		1,200 mg/kg (rabbit)
	LC50 Fish	86 mg/l (Fish)
Dermal	LD50	1,000 mg/kg (Guinea pig)
		500 mg/kg (rabbit)
Inhalative	LC50/4 h	7.1 mg/l (rat)
162881-26	-7 Organop	hosphine Oxide
Oral	LD50	>2,000 mg/kg (rat)
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

AU

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XTTM HydroTM

(Contd. of page 5)

#### 12 Ecological Information

· Toxicity

Aquatic toxicity:	ath a amil ata
109-16-0 Triethylene Glycol Dim	-
EC50	>100 mg/kg (Algae)
Biodegradability	28 days (Aerobic) (Biodegradability testing)
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)
72869-86-4 Diurethane Dimethac	crylate
EC50	>0.6 mg/kg (Algae)
Biodegradability	28 days (Aerobic) (Biodegradability testing)
13463-67-7 Titanium Dioxide	
EC50	>100 mg/kg (Algae)
	>1,000 mg/kg (Fish)
79-41-4 Methacrylic Acid	
EC50	17,000 mg/kg (Algae)
	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
162881-26-7 Organophosphine O	Dxide Dxide
EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)
EC50 (static) Aqua toxicity	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates,

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Dispose of contents/container in accordance with international, federal, state, and local regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

ΑU

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XT<sup>TM</sup> Hydro<sup>TM</sup>

(Contd. of page 6)

not regulated
not regulated
not regulated
not regulated
Not applicable.
Not Applicable
Marpol
Not applicable.

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian In	· Australian Inventory of Industrial Chemicals			
109-16-0	Triethylene Glycol Dimethacrylate			
72869-86-4	Diurethane Dimethacrylate			
13463-67-7	Titanium Dioxide			
	Trade Secret			
3290-92-4	TMPTMA			
79-41-4	Methacrylic Acid			
10287-53-3	Ethyl-4-Dimethylamino Benzoate			
51274-00-1	Yellow Iron Oxide			
10373-78-1	Camphorquinone			
162881-26-7	Organophosphine Oxide			
1332-37-2	Red Iron Oxide			
10163-15-2	Sodium Monofluorophosphate			
Ctan dand for	Ctandard for the Uniform Caledrine of Medicines and Deigons			

#### · Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

#### · Australia: Priority Existing Chemicals

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

Printing date 28.07.2023 Revision: 28.07.2023

Trade name: UltraSeal XTTM HydroTM

(Contd. of page 7)

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases from Section 3

H227 Combustible liquid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

 $vPvB: very\ Persistent\ and\ very\ Bioaccumulative$ 

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

\* \* Data compared to the previous version altered.

ΑU