



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: GINGIFAST RIGID – BASE, CATALYST & SEPARATOR

Manufacturer: Zhermack S.p.a

SDS: 4 November 2027

Supplier Details: Henry Schein New Zealand

243-249 Bush Road, Rosedale, Auckland, 0632 PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6

HSNO Group Standard: Dental Products Flammable Group Standard 2020 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – August 2023

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 1/12

# C401520, C430001, C203230 GINGIFAST RIGID - BASE

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

 Code:
 C401520, C430001, C203230

 Product name
 GINGIFAST RIGID - BASE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use For professional use only. Addition silicone for the reproduction of gingival masks.

1.3. Details of the supplier of the safety data sheet

Name Zhermack S.p.a
Full address Via Bovazecchino 100
District and Country 45021 Badia Polesine (RO)

Tel. +39 0425-597611 Fax +39 0425-597689

e-mail address of the competent person

responsible for the Safety Data Sheet msds@zhermack.com

1.4. Emergency telephone number

For urgent inquiries refer to UK Emergency number: 844 892 0111 (24 hours)

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

Hazard classification and indication:

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

Precautionary statements: --

#### 2.3. Other hazards

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 2/12

# C401520, C430001, C203230 GINGIFAST RIGID - BASE

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%. There is no exposure to breathable free crystalline silica during normal use of this product. For more information see section 11.

# **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

**CRISTOBALITE** 

CAS 14464-46-1 19 ≤ x < 29 STOT RE 1 H372

EC 238-455-4 INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

#### **SECTION 5. Firefighting measures**

# C401520, C430001, C203230 GINGIFAST RIGID - BASE

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 3/12

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

# Zhermack S.p.a Revision nr. 3 Dated 22/09/2017 C401520, C430001, C203230 GINGIFAST RIGID - BASE Page n. 4/12

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3. Specific end use(s)

See section 1.2.

#### **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

DNK Danmark Graensevaerdier per stoffer og materialer

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

NLD Nederland Databank of the social and Economic Concil of Netherlands (SER) Values,

AF 2011:18

SWE Sverige Occupational Exposure Limit Values, AF 2011:18

TLV-ACGIH ACGIH 2016

CRISTOBALITE						
Threshold Limit Value Type	Country	TWA/8h		STEL/15min		
21 -	,	mg/m3	ppm	mg/m3	ppm	
TLV	DNK	0,15		<b>J</b>		RESP
VLEP	FRA	0,05				RESP

# C401520, C430001, C203230 GINGIFAST RIGID - BASE

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 5/12

RESP

 VLEP
 ITA
 0,05
 RESP
 (USA-NIOSH)

 MAC
 NLD
 0,075
 RESP

TLV-ACGIH 0.025

SWF

Legend:

MAK

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

0.05

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

#### **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance fluid
Colour pink
Odour odourless

# C401520, C430001, C203230 GINGIFAST RIGID - BASE

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 6/12

Odour threshold Not applicable Not applicable Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point Not available Evaporation Rate Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density Not available Solubility insoluble in water Partition coefficient: n-octanol/water Not applicable Auto-ignition temperature Not available Decomposition temperature Not available Viscosity Not available Not explosive Explosive properties Not available Oxidising properties

#### 9.2. Other information

Information not available

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

# C401520, C430001, C203230 **GINGIFAST RIGID - BASE**

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 7/12

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Information not available

## **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

# **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture: Not classified (no significant component)

LD50 (Oral) of the mixture: Not classified (no significant component)

LD50 (Dermal) of the mixture: Not classified (no significant component)

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD** Does not meet the classification criteria for this hazard class

CRISTOBALITE

Acute Toxicity: No data available.

Irritation/Corrosion

Skin irritation: Not irritating (MSDS supplier). Eye irritation: Slightly irritating (MSDS supplier).

# C401520, C430001, C203230 GINGIFAST RIGID - BASE

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 8/12

Sensitization: Not sensitizing (MSDS supplier).

Mutagenicity: Does not meet the classification criteria for this hazard class (MSDS supplier).

Carcinogenicity: IARC (group 1), NTP (RAHC), ACGIH (A2) (IARC).

Toxicity to reproduction: Does not meet the classification criteria for this hazard class (MSDS supplier).

Toxicity for aspiration: Not applicable.

STOT Repeated Exposure: Adverse effects on lungs (fibrosis-silicosis)(MSDS supplier).

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France).

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003).

There is a body of evidence supporting the fact that increased cancer risk would not be limited to people already suffering from silicosis. According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

"For the purposes of classification of health hazards (part 3), the route of exposure, information on mechanisms and metabolism studies are useful for determining the relevance of effects in humans. If this information raises doubts as to their relevance in humans, in spite of the indisputable data legitimacy and quality, a lower classification may be justified. When there is scientific evidence that the mechanism or mode of action is not relevant to humans, the substance or mixture should not be classified (annex I, section 1.1.1.5, EC Regulation 1272/2008)".

Monitoring activities conducted at the company related to possible inhalation exposure, in accordance with industrial hygiene standards for paste and fluid products, showed levels of exposure to free crystalline silica (breathable part) below the limit of quantification of the method, therefore exposure is not expected during the use indicated in section 1.2 for this specific product.

However, the actual levels of free crystalline silica (breathable part) present in the workplace must be obtained through monitoring as required by regulations for the safety and health of workers.

#### **SECTION 12. Ecological information**

#### 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

CRISTOBALITE

NOT rapidly degradable

#### 12.3. Bioaccumulative potential

Information not available

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

# Zhermack S.p.a Revision nr. 3 Dated 22/09/2017 C401520, C430001, C203230 GINGIFAST RIGID - BASE Page n. 9/12

Information not available

SECTION 13. Disposal considerations
13.1. Waste treatment methods
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  CONTAMINATED PACKAGING  Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.
SECTION 14. Transport information
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.
14.1. UN number
Not applicable
14.2. UN proper shipping name
Net and Sabla
Not applicable
14.3. Transport hazard class(es)
Not applicable
. Vot applicable
14.4. Packing group
Not applicable
14.5. Environmental hazards
Not applicable
14.6. Special precautions for user

# Zhermack S.p.a Revision nr. 3 Dated 22/09/2017 C401520, C430001, C203230 GINGIFAST RIGID - BASE Page n. 10/12

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

#### **SECTION 16. Other information**

Revision nr. 3 Dated 22/09/2017

Printed on 22/09/2017

Page n. 11/12

# C401520, C430001, C203230 **GINGIFAST RIGID - BASE**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

H372 Causes damage to organs through prolonged or repeated exposure.

**EUH210** Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- Regulation (EC) 1272/2008 (CLP) of the European Parliament
   Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

#### Revision nr. 3 Zhermack S.p.a Dated 22/09/2017 Printed on 22/09/2017 C401520, C430001, C203230 **GINGIFAST RIGID - BASE** Page n. 12/12

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: 01/02/03/04/07/09/10/11/12/13/14/15/16.

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 1/12

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

# Safety data sheet

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: C401520, C430001, C203230
Product name GINGIFAST RIGID - CATALYST

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use For professional use only. Addition silicone for the reproduction of gingival masks.

#### 1.3. Details of the supplier of the safety data sheet

Name Zhermack S.p.a
Full address Via Bovazecchino 100
District and Country 45021 Badia Polesine (RO)

Tel. +39 0425-597611 Fax +39 0425-597689

e-mail address of the competent person

responsible for the Safety Data Sheet msds@zhermack.com

#### 1.4. Emergency telephone number

For urgent inquiries refer to UK Emergency number: 844 892 0111 (24 hours)

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments.

Hazard classification and indication:

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

Precautionary statements: --

#### 2.3. Other hazards

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 2/12

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%. There is no exposure to breathable free crystalline silica during normal use of this product. For more information see section 11.

# **SECTION 3. Composition/information on ingredients**

#### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

**CRISTOBALITE** 

CAS 14464-46-1 5 ≤ x < 10 STOT RE 1 H372

EC 238-455-4 INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

#### **SECTION 5. Firefighting measures**

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 3/12

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 4/12

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3. Specific end use(s)

See section 1.2.

#### **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

DNK Danmark Graensevaerdier per stoffer og materialer

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

NLD Nederland Databank of the social and Economic Concil of Netherlands (SER) Values,

AF 2011:18

SWE Sverige Occupational Exposure Limit Values, AF 2011:18

TLV-ACGIH ACGIH 2016

CRISTOBALITE						
Threshold Limit Value Type	Country	TWA/8h		STEL/15min		
Туре	Country	TVVAVOIT		31 LL/ 13111111		
		mg/m3	ppm	mg/m3	ppm	
TLV	DNK	0,15				RESP
VLEP	FRA	0,05				RESP

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 5/12

 VLEP
 ITA
 0,05
 RESP
 (USA-NIOSH)

 MAC
 NLD
 0,075
 RESP

 MAK
 SWE
 0.05
 RESP

TLV-ACGIH 0,025

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

#### **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance fluid
Colour white
Odour odourless

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 6/12

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

Odour threshold Not applicable Not applicable Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point Not available Evaporation Rate Not available Flammability of solids and gases Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Not available Relative density Solubility insoluble in water Partition coefficient: n-octanol/water Not applicable Not available Auto-ignition temperature Decomposition temperature Not available Viscosity Not available Not explosive Explosive properties Oxidising properties Not available

#### 9.2. Other information

Information not available

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

# C401520, C430001, C203230 **GINGIFAST RIGID - CATALYST**

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 7/12

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

Information not available

## **SECTION 11. Toxicological information**

#### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture: Not classified (no significant component)

LD50 (Oral) of the mixture: Not classified (no significant component)

LD50 (Dermal) of the mixture: Not classified (no significant component)

#### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY** 

Does not meet the classification criteria for this hazard class REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD** 

Does not meet the classification criteria for this hazard class

# CRISTOBALITE

Acute Toxicity: No data available.

Irritation/Corrosion

Skin irritation: Not irritating (MSDS supplier). Eye irritation: Slightly irritating (MSDS supplier).

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 8/12

Sensitization: Not sensitizing (MSDS supplier).

Mutagenicity: Does not meet the classification criteria for this hazard class (MSDS supplier).

Carcinogenicity: IARC (group 1), NTP (RAHC), ACGIH (A2) (IARC).

Toxicity to reproduction: Does not meet the classification criteria for this hazard class (MSDS supplier).

Toxicity for aspiration: Not applicable.

STOT Repeated Exposure: Adverse effects on lungs (fibrosis-silicosis)(MSDS supplier).

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France).

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003).

There is a body of evidence supporting the fact that increased cancer risk would not be limited to people already suffering from silicosis. According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

"For the purposes of classification of health hazards (part 3), the route of exposure, information on mechanisms and metabolism studies are useful for determining the relevance of effects in humans. If this information raises doubts as to their relevance in humans, in spite of the indisputable data legitimacy and quality, a lower classification may be justified. When there is scientific evidence that the mechanism or mode of action is not relevant to humans, the substance or mixture should not be classified (annex I, section 1.1.1.5, EC Regulation 1272/2008)".

Monitoring activities conducted at the company related to possible inhalation exposure, in accordance with industrial hygiene standards for paste and fluid products, showed levels of exposure to free crystalline silica (breathable part) below the limit of quantification of the method, therefore exposure is not expected during the use indicated in section 1.2 for this specific product.

However, the actual levels of free crystalline silica (breathable part) present in the workplace must be obtained through monitoring as required by regulations for the safety and health of workers.

#### **SECTION 12. Ecological information**

#### 12.1. Toxicity

Information not available

#### 12.2. Persistence and degradability

CRISTOBALITE

NOT rapidly degradable

#### 12.3. Bioaccumulative potential

Information not available

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 9/12

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

Information not available

# **SECTION 13. Disposal considerations**

13.1. Waste treatment methods
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.  Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  CONTAMINATED PACKAGING  Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.
SECTION 14. Transport information
The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.
14.1. UN number
Not applicable
14.2. UN proper shipping name
Not applicable
14.3. Transport hazard class(es)
Not applicable
14.4. Packing group
Not applicable
14.5. Environmental hazards
Not applicable
14.6. Special precautions for user

# C401520, C430001, C203230 GINGIFAST RIGID - CATALYST

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 10/12

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

# **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

# **SECTION 16. Other information**

Revision nr. 3 Dated 22/09/2017

Printed on 22/09/2017

Page n. 11/12

# C401520, C430001, C203230 **GINGIFAST RIGID - CATALYST**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

H372 Causes damage to organs through prolonged or repeated exposure.

**EUH210** Safety data sheet available on request.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- Regulation (EC) 1272/2008 (CLP) of the European Parliament
   Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

# C401520, C430001, C203230 **GINGIFAST RIGID - CATALYST**

Revision nr. 3

Dated 22/09/2017

Printed on 22/09/2017

Page n. 12/12

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:
The following sections were modified:
01 / 02 / 03 / 04 / 07 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16



# Revision nr. 6 Dated 04/11/2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Product Name: SEPARATOR FOR GINGIFAST

Code: C400888, C203227, C203232, C401500, C401520

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

For professional use only. Isolator between two surfaces.

#### 1.3. Details of the supplier of the safety data sheet

Name

Zhermack S.p.a

Via Bovazecchino 100

45021 Badia Polesine (RO)

Italy

tel. +39 0425-597611

fax +39 0425-597689

Competent person responsible for the safety data sheet:

msds@zhermack.com

#### 1.4. Emergency telephone number

UK Emergency number: 999 (24 hours)

#### SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Flam. Liq. 2, H225 Highly flammable liquid and vapour.

Eye Irrit. 2, H319 Causes serious eye irritation.

STOT SE 3, H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

#### Hazard pictograms:



#### Danger

#### Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Revision nr. 6 Page n. 1 of 11



P312 Call a POISON CENTER if you feel unwell.

**Special Provisions:** 

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

ethyl acetate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards:

No other hazards

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not Applicable

#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 80% - < 90%	ethyl acetate	Index number: CAS: EC:		STOT SE 3 H336 May cause drowsiness or dizziness. Flam. Liq. 2 H225 Highly flammable liquid and vapour. Eye Irrit. 2 H319 Causes serious eye irritation. EUH066 Repeated exposure may cause skin dryness or cracking.
				Specific Concentration Limits: C >= 10%: EUH066

#### SECTION 4: First aid measures

# 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

None

Revision nr. 6 Page n. 2 of 11



#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### SECTION 5: Firefighting measures

# 5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

#### 6.4. Reference to other sections

See also section 8 and 13

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

# 7.2. Conditions for safe storage, including any incompatibilities

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.



Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

See section 10.5.

Instructions as regards storage premises:

Cool and adequately ventilated.

#### 7.3. Specific end use(s)

See section 1.2.

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

SEPARATOR FOR GINGIFAST ethyl acetate - CAS: 141-78-6

OEL Type	TWA		Duratio n	STEL		Duratio n	Notes	Country
MAK	750	200	8h	1500	400	15min		GERMANY
IVI/ (IX	mg/m3	ppm	011	mg/m3	ppm	10111111		OLI (W) (IV)
AGW	730	200	8h	1460	400	15min		GERMANY
7.077	mg/m3	ppm	011	mg/m3	ppm	10111111		OLI (W) (IV)
MAK	730	200	8h	1460	400	15min		SWITZERLA
	mg/m3	ppm		mg/m3	ppm			ND
AK	1400		8h	1400		15min		HUNGARY
	mg/m3			mg/m3				
HTP	730	200	8h	1470	400	15min		FINLAND
	mg/m3	ppm		mg/m3	ppm			
MAK	734	200	8h	1468	400	15min		AUSTRIA
	mg/m3	ppm		mg/m3	ppm			
NDS/NDSCh	200		8h	600		15min		POLAND
	mg/m3			mg/m3				
NGV/KGV	550	150	8h	1100	300	15min		SWEDEN
	mg/m3	ppm		mg/m3	ppm			
OELV		200	8h		400	15min		IRELAND
		ppm			ppm			
VLEP	734	200	8h	1468	400	15min		ITALY
	mg/m3	ppm		mg/m3	ppm			
RV	200	54 ppm	8h	1468	400	15min		LATVIA
	mg/m3			mg/m3	ppm			
TLV	400	111	8h	500	139	15min		ROMANIA
	mg/m3	ppm		mg/m3	ppm			
TLV	540	150	8h	1080	300	15min		DENMARK
	mg/m3	ppm		mg/m3	ppm			
VLEP	734	200	8h	1468	400	15min		FRANCE
	mg/m3	ppm		mg/m3	ppm			
VLEP	734	200	8h	1468	400	15min		BELGIUM
	mg/m3	ppm		mg/m3	ppm			
WEL	730	200	8h	1460	400	15min		UNITED
	mg/m3	ppm		mg/m3	ppm			KINGDOM
VLA	1460	400	8h					SPAIN
	mg/m3	ppm						
EU	734	200	8h	1468	400			
	mg/m3	ppm		mg/m3	ppm			
TLV-ACGIH		400	8h				URT and	



	ppm			eye irr	
ACGIH	400	8h		URT and	
	ppm			eye irr	

**DNEL Exposure Limit Values** 

ethyl acetate - CAS: 141-78-6

Worker Professional: 1468 mg/m3 - Exposure: Human Inhalation - Frequency: Short

Term, local effects

Worker Professional: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long

Term, local effects

Worker Professional: 1468 mg/m3 - Exposure: Human Inhalation - Frequency: Short

Term, systemic effects

Worker Professional: 734 mg/m3 - Exposure: Human Inhalation - Frequency: Long

Term. systemic effects

Worker Professional: 63 mg/kg bw/d - Exposure: Human Dermal - Frequency: Long

Term, systemic effects

PNEC Exposure Limit Values

ethyl acetate - CAS: 141-78-6

Target: Fresh Water - Value: 0.26 mg/l Target: Marine water - Value: 0.026 mg/l Target: Soil (agricultural) - Value: 0.24 mg/kg

Target: Marine water sediments - Value: 0.125 mg/kg Target: Freshwater sediments - Value: 1.25 mg/kg

8.2. Exposure controls

Precautionary measures:

Give adequate ventilation to the premises where the product is stored and/or handled.

Eye protection:

Wear airtight protective goggles (EN 166).

Protection for skin:

Wear professional overalls and safety footwear (EN 14605).

Protection for hands:

Suitable material:

NBR (nitrile rubber - EN 374).

The following should be considered when choosing work glove material (EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Respiratory protection:

Mask with filter "A", brown colour

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered (e.g. TLV-TWA).

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid		



Colour:	Opaque		
Odour:	Typical of solvent		
Melting point/freezing	Not available		
point:			
Boiling point or initial	76	ASTM D	
boiling point and boiling		1120	
range:			
Flammability:	Flam. Liq. 2, H225		
Lower and upper explosion	Not available		
limit:			
Flash point:	-1 ° C	ASTM	
		D93-19	
Auto-ignition temperature:	Not available		
Decomposition	Not available		
temperature:			
pH:	Not Relevant		
Kinematic viscosity:	Not available		
Solubility in water:	Insoluble		
Solubility in oil:	Not available		
Partition coefficient	Not available		
n-octanol/water (log value):			
Vapour pressure:	Not available		
Density and/or relative	0.93 g/cm3 (calculated)		
density:			
Relative vapour density:	Not available		
	Particle characteristics:		
Particle size:	Not available		

#### 9.2. Other information

No other relevant information

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 10.4. Conditions to avoid

Heat, direct sunlight.

Avoid bunching of electrostatic charges.

Avoid all sources of ignition.

### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### 10.6. Hazardous decomposition products

flammable gases / vapors

acetic acid

# SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

Revision nr. 6 Page n. 6 of 11



#### SEPARATOR FOR GINGIFAST

a) acute toxicity

Not classified

b) skin corrosion/irritation Not classified

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Not classified

e) germ cell mutagenicity

Not classified

f) carcinogenicity

Not classified

g) reproductive toxicity

Not classified

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

i) aspiration hazard

Not classified

Toxicological information of the main substances found in the product:

ethyl acetate - CAS: 141-78-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 4934 mg/kg - Source: (OECD 401, MSDS supplier).

Test: LD50 - Route: Skin - Species: Rabbit > 18000 mg/kg - Source: (MSDS supplier).

Test: LC50 - Route: Inhalation - Species: Rat 56 mg/l - Duration: 4h - Source: (SDS supplier).

b) skin corrosion/irritation:

Species: Rabbit - Based on available data, the classification criteria are not met - Source: (OECD TG 404, MSDS supplier).

c) serious eye damage/irritation:

Species: Rabbit - Based on available data, the classification criteria are not met - Source: (OECD TG 405, MSDS supplier).

d) respiratory or skin sensitisation:

Species: Guinea pig - Based on available data, the classification criteria are not met - Source: (OECD TG 406, MSDS supplier).

#### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

#### SECTION 12: Ecological information

#### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. SEPARATOR FOR GINGIFAST

Not classified for environmental hazards

Revision nr. 6 Page n. 7 of 11



Based on available data, the classification criteria are not met

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 230 mg/l - Duration h: 96h (Salmo gairdneri, MSDS

supplier).

Endpoint: EC50 - Species: Daphnia 3090 mg/l - Duration h: 24h (Daphnia magna, DIN

38412, MSDS supplier).

Endpoint: EC50 - Species: Algae 3300 mg/l - Duration h: 48h (Scenedesmus

subspicatus, MSDS supplier).

Endpoint: NOEC - Species: Algae > 100 mg/l - Duration h: 72h (Desmodesmus

subspicatus, MSDS supplier).

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia 2.4 mg/l - Duration h: 21d (Daphnia magna,

MSDS supplier).

12.2. Persistence and degradability

ethyl acetate - CAS: 141-78-6

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

Not available

12.4. Mobility in soil

Not available

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

None

# SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

# SECTION 14: Transport information



#### 14.1. UN number or ID number

ADR-UN Number: 1173 IATA-UN Number: 1173 IMDG-UN Number: 1173

14.2. UN proper shipping name

ADR-Shipping Name: ETHYL ACETATE IATA-Shipping Name: ETHYL ACETATE IMDG-Shipping Name: ETHYL ACETATE

14.3. Transport hazard class(es)

ADR-Class: 3
IATA-Class: 3

Revision nr. 6 Page n. 8 of 11



IATA-Label: 3 IMDG-Class: 3

14.4. Packing group

Ш ADR-Packing Group: IATA-Packing group: Ш IMDG-Packing group: Ш

14.5. Environmental hazards

ADR-Environmental Pollutant: No IMDG-Marine pollutant: No

IMDG-EmS: F-E , S-D

14.6. Special precautions for user

ADR-Subsidiary hazards: ADR-S.P.:

ADR-Transport category (Tunnel restriction code): 2 (D/E)

ADR - Hazard identification number: IATA-Passenger Aircraft: IATA-Subsidiary hazards: IATA-Cargo Aircraft: 364 IATA-S.P.: IATA-ERG: 3L

IMDG-Subsidiary hazards: Category B

IMDG-Stowage and handling: IMDG-Segregation:

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:



Restriction 75

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P5c

WGK Classification (Water hazard class - Verwaltungsvorschrift wassergefährdende Stoffe) WGK1 - Slightly hazardous for water

Lagerklasse according to TRGS 510:

LGK 3: Flammable liquids

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012: None.

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture. Substances for which a Chemical Safety Assessment has been carried out: None

# SECTION 16: Other information

Full text of phrases referred to in Section 3:

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECHA - European Chemical Agency

GESTIS - Information system on hazardous substances of the German Social Accident Insurance

IARC - International Agency for Research on Cancer

IPCS INCHEM - International Programme on Chemical Safety

ISS - Istituto Superiore di Sanità

PubChem - open chemistry database at the National Institutes of Health (NIH)

Revision nr. 6 Page n. 10 of 11



The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.